

TEL 603-477-2090
EMAIL Sales@ratools.com
WEB www.ratools.com

# Hydraulic RatPak Gen 3™





Highly portable and effective hydraulic breaching toolkit in a custom made backpack. Quick disconnect fittings allow operator to switch tools depending on mission. Door pusher, jamb spreader, bolt cutter, and hydraulic wedge can all be powered easily and quietly from dual stage 10,000 psi pump. US made pack has padded shoulder and waist straps for ultimate mobility.

#### Pack Features:

- · Adjustable padded shoulder straps and adjustable padded hip belt
- · Rigid back panel designed to work with hard armor
- · Loop handle on top to lift pack
- MOLLE attachable pouches available for Bolt Cutter and RatWedge
- Color: Black

HRP2-3			
Item	Part #	Weight	
Door pusher	HDP4	7.5 lbs	
Jamb Spreader		5.7 lbs	
Pump with Backpack		14.6 lbs	

HRP3-3		
Item	Part #	Weight
Door pusher	HDP4	7.5 lbs
Jamb Spreader		5.7 lbs
Bolt Cutter	HBC30	6.8 lbs
Pump with Backpack		14.6 lbs

HRP4-3			
Item	Part #	Weight	
Door pusher	HDP4	7.5 lbs	
Jamb Spreader		5.7 lbs	
Bolt Cutter	HBC30	6.8 lbs	
RatWedge	HS4	7.0 lbs	
Pump with Backpack		14.6 lbs	







## HRP SERIES TECHNICAL SPECIFICATIONS

#### Door Pusher: HDP4

- 4 inch (102mm) stroke
- 10,000 lbs. (44kN) of force
- Includes quick coupler
- Working Pressure: 10,000psi (700 bar)
- Weight: 7.5 lbs. (3.4Kg)
- Dimensions: 10.3 inch x 4.9 inch x 3.7 inch (264mm x 114mm x 95mm)

#### Jamb Spreader Bar: JS41

- Screws onto end of HDP4 to create jamb spreader
- For use on jambs between 26 inches and 41 inches (66 cm and 104cm)
- 10,000 lbs. (44kN) of force
- Working Pressure: 10,000psi (700 bar)
- Weight: 5.7 lbs. (2.6Kg)

#### Hydraulic Bolt Cutter: HBC 30 (Included in HRP3 and HRP4)

- Suitable for cutting metal
- Drop-Forged steel alloy cutting jaws. Jaw opening at tip: 0.75 inch (18mm)
- Cutting capacity: .27in (7mm) with High Hardness HRC40, and .51in (13mm) with Low Hardness HRC 20
- 40,000 lbs. of cutting force
- Dimensions: 8.3 inch x 7.2 inch x 2.4 inch (213 mm x 184 mm x 59mm)
- Single acting steel cylinder with guick coupler, Working Pressure: 10,000psi
- Weight: 6.8 lbs. (3.1 Kg)





### 3 Ton Spreader: HS4 (Included in HRP4)

- Rated Load: 3 tons (2,720 Kg) at blade tips
- Closed blade height: 0.16 inch (4 mm)
- Extended blade height: 4.33 inch (10.9 cm)
- Arm Width: 2 inch (5.08 cm)
- Length: 13.2 inch (33.6 cm)
- Working Pressure:10,000psi (700 bar)
- Weight: 7 lbs (3.0 Kg)

