

30" MAMAW CLOWN

Copyright 1997

(Use 20" Baby Shay Sh/Pl., 30" Girl Clown Hands, 30" Girl Clown Boots)

FABRICS & NOTIONS

- 1/2 yd. Cotton Print 45" Width - bodice, sleeves
- 2/3 yd. Cotton Print 45" Width - bloomers
- 1/2 yd. Cotton Print 45" Width - skirt
- 5/8 yd. Black Tulle 72" Width - collar/yoke, sleeves
- 1/2 yd. Cotton Print 45" Width - overskirt/flounce, waistband
- 1/4 yd. Cotton Print 45" Width - leggings
- 1 Decorative Button - pin (broach)
- 4 Small Gold Buttons - center front yoke
- 5 Small Snaps
- 7/8 yd. Elastic 1/8" Width - bloomers, sleeves

READ ALL INSTRUCTIONS BEFORE CUTTING FABRICS

- A. *WRST*, indicates With Right Sides Together.
- B. All seams are 1/4" unless otherwise indicated.
- C. Because of size, the bloomers and overskirt/flounce pattern pieces have been cut into 4 pieces each. Tape each pattern piece and its corresponding extensions together before cutting fabrics.

DRESS CONSTRUCTION:

(Pieces A, B, C, & D) (Sleeve Elastic 4 1/2")

1. *WRST*, sew the front and back bodice together at the shoulder seams.

2. Sew in darts on the front and back bodice.

FOR YOKE USE - (Pieces H, J, AA, AH, HH, Q)

3. Cut yoke pattern piece "H" from tulle netting. Baste yoke to dress bodice at the neck.

4. Fold neck ruffle "AA" on the fold line and sew 2 rows of gathering stitches on the raw edge. Pull up gathering threads to fit the neck, pin and sew ruffle to the neckline.

5. Fold yoke ruffle "AH" on the fold line and sew 2 rows of gathering stitches along the raw edge. Pull up threads to a finished length of 23".

6. Machine baste yoke ruffle to outer edge of yoke.

7. Fold under 1/4" on each edge of yoke trim "HH".

Pin yoke trim to the yoke edge covering the yoke ruffle seam allowance. Top stitch both edges of yoke trim. **SEE DIAGRAM.**

8. Finish raw edges of both bodice center back facings with an overlock stitch or turn under 1/8" and straight stitch. Turn under facings and press on the fold line.

9. *WRST*, sew neck binding "J" to the neckline. Clip the neck seam. Fold in the ends, then turn under binding 1/4" and stitch in place, making a small stand-up collar.

10. Turn under facing at center back from neckline to waist and blind stitch.

11. Sew 2 rows of gathering stitches on sleeves between the dots, as indicated on the pattern. Sew in dart on bottom of sleeves.

PATTERN NUMBER DA 1370

BODY PATTERN DA 1369

THE
DOLLING
ARTWORKS

RT. 9 BOX 119

HWY 274

SEVEN POINTS, TX 75143

TEL 903-432-9426

FAX 903-432-9502

ORDERS ONLY

800-886-3655

12. Sew elastic in the sleeve bottoms. **SEE PATTERN FOR PLACEMENT.**

13. Pull up gathering threads, distributing gathers evenly, pin and sew sleeves to bodice.

14. Gather curved edge of sleeve netting "Q" to fit where the sleeves are gathered. Stitch to sleeve seam allowance *inside* the sleeves. This helps keep the upper sleeve puffed.

15. Sew underarm sleeve seams. Hem the sleeves.

16. Mark the center front of the dress skirt with a fabric pencil. Sew two rows of gathering stitches on the skirt top.

17. Pull up gathering threads to a finished length of 12". This allows for 1/4" extension at each end for center back seam allowance. Matching skirt center front to bodice center front, pin and sew skirt to bodice.

18. *WRST*, sew center back skirt seam leaving the top 3" open.

19. Turn under bottom edge of skirt 1/4" and stitch. Then turn under a 2 1/2" hem and blind stitch in place. Press.

20. Sew snaps on bodice backs and gold buttons on the yoke front. **SEE PATTERN FOR PLACEMENT.**

OVERSKIRT/FLOUNCE CONSTRUCTION:

(Pieces "E" and "EE")

21. Fold fabric under 1/8" twice and sew a shirttail hem on bottom of flounce. A rolled hem attachment works well for this task.

22. Sew 2 rows of gathering stitches across the top and on the sides. **SEE PATTERN FOR PLACEMENT.**

Pull up gathering threads to measure 12" finished length.

23. Position waistband "EE" on the gathered edge of the flounce. The waistband will extend past the flounce 1/4" on each end, pin and sew.

24. Tack the 1/4" extension back toward the gathered edge. Fold over waistband 1/4" twice and blind stitch to the flounce and waistband seam.

25. Sew small snaps on the ends of the waistband.

BLOOMERS CONSTRUCTION: (Piece "G")

(Waist Elastic 10") (Leg Elastic 4 1/2")

26. *WRST*, sew the center front and center back seams.

27. Turn under and sew waist casing leaving a small opening for inserting elastic. Insert 1/8" elastic in casing lapping elastic ends one over the other. Sew elastic ends together. Close the casing opening with a machine stitch.

28. Turn under lower legs on the fold line. **SEE PATTERN FOR PLACEMENT.**

29. Zigzag 1/8" elastic on the lower legs. **SEE PATTERN FOR PLACEMENT.** Anchor elastic with two or three stitches at the start, then zigzag over the elastic, pulling elastic as you sew. Back stitch a few stitches at the end. Prepare both legs.

30. Sew leg inseam catching elastic ends in the seams. Press.

LEGGINGS CONSTRUCTION: (Piece "F")

31. Cut leggings with the stripes going around the legs. Using a basting stitch, sew one side of legging directly to the doll leg. Starting at the boot, sew toward the top. Bring fabric around the leg, fold under 1/4" seam allowance and matching stripes, blind stitch the legging in place. Prepare both legs.

32. NOTE: Leggings can also be cut and sewn in with the legs as the body is being made. This will give the most appealing appearance.

THIS PATTERN CONTAINS 20 PIECES.

- A -- Bodice Front
- AA - Yoke Neck Ruffle
- AH - Yoke Ruffle
- B -- Bodice Back
- C -- Sleeves
- D -- Dress Skirt
- E -- Overskirt/Flounce - "A"
- E -- Overskirt/Flounce - EXTENSION "B"
- E -- Overskirt/Flounce - EXTENSION "C"
- E -- Overskirt/Flounce - EXTENSION "D"
- EE - Overskirt/Flounce Waistband
- F -- Leggings
- G -- Bloomers - "A"
- G -- Bloomers - EXTENSION "B"
- G -- Bloomers - EXTENSION "C"

G -- Bloomers - EXTENSION "D"

H -- Yoke

HH - Yoke Trim

J -- Yoke Neck Binding

Q -- Sleeve Netting

DIAGRAM FOR YOKE -






DIAGRAM FOR OVERSKIRT/FLOUNCE





D

Tape to "Extension - B" before cutting fabric

G
DA 1370
30" MAMAW CLOWN
BLOOMERS - Extension "D"
© 1997


Sew Elastic Here

Inseam

On Fold

DA 1370
30" Mamaw Clown
YOKE
CUT 1 - Black Tulle
© 1997

H



Tape to EXTENSION "B" before cutting fabric.

Tape to EXTENSION "C" before cutting fabric.

E

DA 1370
30" MAMAW CLOWN
DRESS OVERSKIRT/FLOUNCE - Extension "D"

gather





J
DA 1370
30" MAMAW CLOWN
YOKE NECK BINDING
Cut 1 - Black Tulle.
© 1997

FOLD LINE



PATTERN NUMBER DA 1370
Copyright 1997



AH
DA 1370
30" Mamaw Clown
YOKE RUFFLE
CUT 1 - Black Tulle
44" x 1 1/2"




HH
DA 1370
30" Mamaw Clown
YOKE TRIM
CUT 1 - Bias (Black Tulle)
24" x 1"

EE
DA 1370
30" Mamaw Clown
OVERSKIRT/FLOUNCE
WAISTBAND
CUT 1 - Cotton Print
12 1/2" x 2 1/2"







Center Back Seam



F

DA 1370

30" MAMAW CLOWN
LEGGINGS
CUT 2 - - Knit Stripe
© 1997

Center Back Seam

inside leg

Center Back

CASING

G

DA 1370

30" MAMAW CLOWN
BLOOMERS - "A"
CUT 2 - Cotton Print

© 1997



Tape to EXTENSION "B" before cutting fabric.

Tape to EXTENSION "B" before cutting fabric.

A

