BURNT HILLS

ICONIC COLLECTION





SPECIFICATIONS

MANUFACTURED: MADE IN CANADA

WOOD ORIGIN: NORTH EASTERN/CENTRAL USA

WOOD SPECIES: WHITE OAK
TYPE: ENGINEERED

GRADE: AVAILABLE IN CHARACTER OR SELECT

SHADE: DARK SURFACE: SANDED

EDGES: MICROBEVELLED (PLANK - LONG SIDES ONLY)

THICKNESS: 20 MM (3/4") WITH 6 MM WEAR LAYER *TOP LAYER

THICKNESS IS MEASURED BEFORE THE FINISHING

PROCESS.

NAMED AFTER A NEW YORK HAMLET THAT WAS HISTORICALLY SET ABLAZE, BURNT HILLS WHITE OAK PLANKS ARE FITTINGLY BLACK, AND UNDENIABLY STRIKING. OWING TO ITS REVERSE HIGHLIGHTED GRAIN, HINTS OF GREY COME THROUGH FROM VARIOUS ANGLES, GIVING EACH PLANK AN ELEVATED LOOK. LAVISH AND ELEGANT, THESE PROMINENT HARDWOODS LEND THEMSELVES TO A HEAVIER, MORE TRADITIONAL SENSIBILITY.

CONSTRUCTION: PURECRAFT 3-LAYER OR

WBP BALTIC BIRCH PLYWOOD

FINISH: HARDWAX OIL (UV CURED)

PLANK WIDTHS: 178 MM / 229 MM / 280 MM (7" / 9" / 11")

PLANK LENGTHS: 914 MM - 3581 MM (36" - 141")

HERRINGBONE DIMENSIONS: 4" X 20" (101.6 MM X 508 MM)

CHEVRON DIMENSIONS: 4" X 16" (101.6 MM X 406.4 MM)

COLOUR VARIATION: V1 - SLIGHT VARIATION

JULUUR VARIATION:

CERTIFICATIONS:



CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F)

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.







TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	ASTM E 648-17 Class II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA

INSTALLATION

TYPE

Full Glue Down

Nail Down

Nail Down

Floating

Over Underfloor Heating

RECOMMENDATION

YES - RECOMMENDED

YES - WITH GLUE ASSIST

NOT RECOMMENDED

YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.