

# DEL MAR

ICONIC

**Northern**  
WIDE PLANK



NESTLED IN THE SEASIDE TOWN OF DEL MAR, THE TORREY IS AMONG THE RAREST OF NORTH AMERICA'S PINE TREES. DEL MAR PLANKS ARE AN HOMAGE TO THIS FLEETING SPECIES OF EVERGREEN. WITH ITS NEUTRAL TONE, SUBTLE OAK GRAIN, AND BRUSHED FINISH, THE MOOD IS LIGHT, BRIGHT, AND COZY. FROM MALIBU TO MONTAUK, THE CALIFORNIA BEACH HOUSE SETTING IS ALWAYS IN SEASON.

## SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA
WOOD ORIGIN:	NORTH EASTERN/CENTRAL USA
WOOD SPECIES:	WHITE OAK
TYPE:	ENGINEERED
GRADE:	AVAILABLE IN CHARACTER OR SELECT
SHADE:	LIGHT
SURFACE:	BRUSHED
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	20 MM (3/4") WITH 6 MM WEAR LAYER*TOP LAYER THICKNESS IS MEASURED BEFORE THE FINISHING PROCESS. PROCESSES SUCH AS PLANING WILL AFFECT THE OVERALL THICKNESS.
CONSTRUCTION:	WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	178 mm / 229 mm / 280 mm (7" / 9" / 11")
PLANK LENGTHS:	914 MM - 3581 MM (36" - 141")**NOMINAL LENGTHS MEASURED PRIOR TO FINISHING. AVERAGE LENGTHS ARE 6'-7'.
HERRINGBONE DIMENSIONS:	4" X 20" (101.6 MM X 508 MM)
CHEVRON DIMENSIONS:	4" X 16" (101.6 MM X 406.4 MM)
COLOUR VARIATION:	V2 - MODERATE VARIATION
CERTIFICATIONS:	

## CLEANING AND CARE

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors.

## TECHNICAL PERFORMANCE

### ESSENTIAL CHARACTERISTICS

Reaction to fire
Emission of Formaldehyde
Janka Hardness Rating
Post Consumer Recycled Content %

### PERFORMANCE

ASTM E 648-17 Class II
E1 / CARB 2 compliant
1,360 lbf (6,000 N)
NA

## INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	YES - RECOMMENDED
Nail Down	YES - WITH GLUE ASSIST
Floating	NOT RECOMMENDED
Over Underfloor Heating	YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.



FSC® AVAILABLE UPON REQUEST