GASPE

ICONIC COLLECTION





SPECIFICATIONS

MANUFACTURED: MADE IN CANADA

WOOD ORIGIN: NORTH EASTERN/CENTRAL USA

WOOD SPECIES: WHITE OAK
TYPE: ENGINEERED
GRADE: CHARACTER
SHADE: LIGHT
SURFACE: SHRUNK

EDGES: MICROBEVELLED (PLANK - LONG SIDES ONLY)

THICKNESS: 20 MM (3/4") WITH 6 MM WEAR LAYER *TOP LAYER

THICKNESS IS MEASURED BEFORE THE FINISHING

PROCESS.

SITUATED IN EASTERN QUEBEC, THE GASPE PENINSULA ENDURES SULTRY SUMMER MONTHS FOLLOWED BY BITTER-COLD WINTERS. RESIDENTS ARE AS RESILIENT AS OUR GASPE PLANKS. RELAXED COLOURATION, WITH MUTED GREY/BROWN MID-TONES, THESE HARDWOODS PERSEVERE GORGEOUSLY THROUGH THE YEARS, MAKING ANY SPACE HOMEY AND INVITING.

CONSTRUCTION: PURECRAFT 3-LAYER OR

WBP BALTIC BIRCH PLYWOOD

FINISH: HARDWAX OIL (UV CURED)

PLANK WIDTHS: 229 MM / 280 MM (9" / 11")

PLANK LENGTHS: 914 MM - 3581 MM (36" - 141")

HERRINGBONE DIMENSIONS: 4" X 20" (101.6 MM X 508 MM)

CHEVRON DIMENSIONS: 4" X 16" (101.6 MM X 406.4 MM)

COLOUR VARIATION: V2 - MODERATE VARIATION

CERTIFICATIONS:

CLEANING AND CARE

TECHNICAL PERFORMANCE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F)

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.







FSC© AVAILABLE UPON REQUEST

ESSENTIAL CHARACTERISTICS Reaction to fire ASTM E 648-17 Class II Emission of Formaldehyde E1 / CARB 2 compliant Janka Hardness Rating Post Consumer Recycled Content % NA

INSTALLATION

TYPE

RECOMMENDATION

Full Glue Down

Nail Down

Nail Down

Floating

Over Underfloor Heating

RECOMMENDATION

YES - RECOMMENDED

YES - WITH GLUE ASSIST

NOT RECOMMENDED

YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.