HUDSON

ICONIC COLLECTION





AS A CLIENT, YOU EXPECT THE FLEXIBILITY TO BUILD ON YOUR OWN

PERSONAL VISION. DUE TO ITS GREAT RECEPTIVITY TO -MANY

TECHNIQUES, NORTHERN WIDE PLANK WHITE OAK OFFERS THE

CANVAS FOR YOU TO DO JUST THAT. A SLOW-GROWTH HARDWOOD,

WHITE OAK HAS THE VERSATILITY TO ACHIEVE VIRTUALLY ANY EFFECT

DIFFERENT COLOUR PIGMENT TREATMENTS AND FINISHING

YOU COULD WISH FOR - FROM THE TRADITIONAL TO THE

SPECIFICATIONS

MANUFACTURED: MADE IN CANADA

WOOD ORIGIN: NORTH EASTERN/CENTRAL USA

WOOD SPECIES: WHITE OAK
TYPE: ENGINEERED

GRADE: AVAILABLE IN CHARACTER OR SELECT

SHADE: BROWN
SURFACE: SANDED

EDGES: MICROBEVELLED (PLANK - LONG SIDES ONLY)

THICKNESS: 20 MM (3/4") WITH 6 MM WEAR LAYER *TOP LAYER

THICKNESS IS MEASURED BEFORE THE FINISHING

PROCESS.

CONSTRUCTION: PURECRAFT 3-LAYER OR

WBP BALTIC BIRCH PLYWOOD

FINISH: HARDWAX OIL (UV CURED)

PLANK WIDTHS: 178 MM / 229 MM / 280 MM (7" / 9" / 11")

PLANK LENGTHS: 914 MM - 3581 MM (36" - 141")

HERRINGBONE DIMENSIONS: 4" X 20" (101.6 MM X 508 MM)

CHEVRON DIMENSIONS: 4" X 16" (101.6 MM X 406.4 MM)

COLOUR VARIATION: V1 - SLIGHT VARIATION

CERTIFICATIONS:

CLEANING AND CARE

TECHNICAL PERFORMANCE

AVANT-GARDE.

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F)

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.







FSC© AVAILABLE UPON REQUEST

ESSENTIAL CHARACTERISTICS Reaction to fire ASTM E 648-17 Class II Emission of Formaldehyde E1 / CARB 2 compliant Janka Hardness Rating 1,360 lbf (6,000 N)

Post Consumer Recycled Content % NA

INSTALLATION

TYPE

RECOMMENDATION

Full Glue Down

Nail Down

Nail Down

Floating

Over Underfloor Heating

RECOMMENDATION

YES - RECOMMENDED

YES - WITH GLUE ASSIST

NOT RECOMMENDED

YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.