MILL CREEK

ARTIFAX COLLECTION





RENOWNED FOR ITS STRENGTH, RECLAIMED OAK PERSONIFIES A TIMELESS EXPOSURE TO THE HARSH ELEMENTS OF NATURE THAT ARE EMBEDDED IN EACH PLANK. RETAINING ITS CHARACTERISTIC MARKINGS, SUCH AS NICKS AND NAIL HOLES, RECLAIMED OAK CREATES A STUNNING BALANCE BETWEEN RUSTIC AND SOPHISTICATED DESIGN, RANGING FROM GOLDEN WHISKEY HEWS TO WEATHERED PATINA, ONLY THE MOST STUNNING PLANKS ARE SELECTING FOR OUR HANDCRAFTED FINISHING.

SPECIFICATIONS

MANUFACTURED: MADE IN CANADA

WOOD ORIGIN: EASTERN/CENTRAL USA – OLD BARNS/BUILDINGS

WOOD SPECIES: RECLAIMED OAK
TYPE: ENGINEERED

GRADE: GENUINE RECLAIMED

SHADE: BROWN
SURFACE: FOUNDRY

EDGES: EASED (PLANK - LONG SIDE ONLY)

THICKNESS: 20 MM (3/4") WITH 6 MM WEAR LAYER*TOP LAYER

THICKNESS IS MEASURED BEFORE THE FINISHING PROCESS. PROCESSES SUCH AS PLANING WILL

AFFECT THE OVERALL THICKNESS.

CONSTRUCTION: PURECRAFT 3-LAYER OR

WBP BALTIC BIRCH PLYWOOD

FINISH: HARDWAX OIL (UV CURED)

PLANK WIDTHS: 102 MM - 203 MM (4" - 8") RANDOM WIDTHS**MAY

RECEIVE WIDER WIDTHS. BASED ON AVAILABILITY.

PLANK LENGTHS: 914 MM - 3581 MM (36" - 141")***LENGTHS ARE

NOMINAL AND MAY CONTAIN UP TO 5% SHORTER

THAN MINIMUM LENGTH...

HERRINGBONE DIMENSIONS: 4" X 20" (101.6 MM X 508 MM)

CHEVRON DIMENSIONS: 4" X 16" (101.6 MM X 406.4 MM)

COLOUR VARIATION: V4 - DRAMATIC VARIATION

CERTIFICATIONS:



Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F)

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.







TECHNICAL PERFORMANCE

FSC© AVAILABLE UPON REQUEST

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	ASTM E 648-17 CLASS II
Emission of Formaldehyde	E1 / CARB 2 COMPLIANT
Janka Hardness Rating	1,360 LBF (6,000 N)
Post Consumer Recycled Content %	25

INSTALLATION

TYPE

RECOMMENDATION

Full Glue Down

Nail Down

Nail Down

Floating

Over Underfloor Heating

RECOMMENDATION

YES - RECOMMENDED

YES - WITH GLUE ASSIST

NOT RECOMMENDED

YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.