MONTAUK

ICONIC





RENOWNED FOR ITS FISHING, AND NAMED AFTER THE MONTAUKETT TRIBE, THE TOWN OF MONTAUK IS AS NATURAL AND BEAUTIFULLY WORN AS THE PLANK THAT BEARS ITS NAME. INFUSED WITH RICH, WARM UNDERTONES, THEN LOVINGLY EMBELLISHED WITH A BAND SAW, EACH PLANK HAS THE FEEL OF SUNBAKED DRIFTWOOD WASHED UP ASHORE.

SPECIFICATIONS

MANUFACTURED: MADE IN CANADA

WOOD ORIGIN: NORTH EASTERN/CENTRAL USA

WOOD SPECIES: WHITE OAK
TYPE: ENGINEERED
GRADE: CHARACTER
SHADE: LIGHT
SURFACE: SHRUNK

EDGES: MICROBEVELLED (PLANK - LONG SIDES ONLY)

THICKNESS: 20 MM (3/4") WITH 6 MM WEAR LAYER*TOP LAYER

THICKNESS IS MEASURED BEFORE THE FINISHING

PROCESS. PROCESSES SUCH AS PLANING WILL

AFFECT THE OVERALL THICKNESS.

CONSTRUCTION: WBP BALTIC BIRCH PLYWOOD

FINISH: HARDWAX OIL (UV CURED)

PLANK WIDTHS: 229 mm / 280 mm (9" / 11")

PLANK LENGTHS: 914 MM - 3581 MM (36" - 141")**NOMINAL LENGTHS

MEASURED PRIOR TO FINISHING. AVERAGE

LENGTHS ARE 6'-7'.

HERRINGBONE DIMENSIONS: 4" X 20" (101.6 MM X 508 MM)

CHEVRON DIMENSIONS: 4" X 16" (101.6 MM X 406.4 MM)

COLOUR VARIATION: V2 - MODERATE VARIATION

CERTIFICATIONS:







FSC© AVAILABLE UPON REQUEST

CLEANING AND CARE

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors.

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS

Reaction to fire

ASTM E 648-17 Class II

Emission of Formaldehyde

E1 / CARB 2 compliant

Janka Hardness Rating

1,360 lbf (6,000 N)

Post Consumer Recycled Content %

NA

INSTALLATION

TYPE

RECOMMENDATION

Full Glue Down

Nail Down

Nail Down

Floating

Over Underfloor Heating

RECOMMENDATION

YES - RECOMMENDED

YES - WITH GLUE ASSIST

NOT RECOMMENDED

YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.