MUSKOKA

ICONIC COLLECTION





SPECIFICATIONS

MANUFACTURED: MADE IN CANADA

WOOD ORIGIN: NORTH EASTERN/CENTRAL USA

WOOD SPECIES: WHITE OAK **ENGINEERED** TYPE:

GRADE: AVAILABLE IN CHARACTER OR SELECT

SHADE: BROWN SURFACE: BRUSHED

EDGES: MICROBEVELLED (PLANK - LONG SIDES ONLY) THICKNESS: 20 MM (3/4") WITH 6 MM WEAR LAYER *TOP LAYER THICKNESS IS MEASURED BEFORE THE FINISHING

PROCESS.

CELEBRATED FOR ITS AZURE SKIES, AND BOUNTIFUL WATERS, THE MUSKOKA REGION OF CENTRAL ONTARIO IS HEAVEN ON EARTH. OUR MUSKOKA PLANKS REFLECT THIS SUMMER HAVEN. SPECKLED WITH KNOTS, STAINED SMOKY BROWN WITH A REDDISH MIDTONE, THEN METICULOUSLY WIRE-BRUSHED, EACH PLANK IS A TIMELESS

TESTAMENT TO THE JOYS OF COTTAGE COUNTRY.

CONSTRUCTION: PURECRAFT 3-LAYER OR

WBP BALTIC BIRCH PLYWOOD

FINISH: HARDWAX OIL (UV CURED)

PLANK WIDTHS: 178 MM / 229 MM / 280 MM (7" / 9" / 11")

PLANK LENGTHS: 914 MM - 3581 MM (36" - 141")

HERRINGBONE DIMENSIONS: 4" X 20" (101.6 MM X 508 MM) CHEVRON DIMENSIONS: 4" X 16" (101.6 MM X 406.4 MM) COLOUR VARIATION: V1 - SLIGHT VARIATION

CERTIFICATIONS:



CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F)

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.







TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	ASTM E 648-17 Class II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA

INSTALLATION

TYPE RECOMMENDATION Full Glue Down YES - RECOMMENDED Nail Down YES - WITH GLUE ASSIST NOT RECOMMENDED Floating YES - REFER TO NWP RADIANT HEAT GUIDE Over Underfloor Heating

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.