CHABLIS

TANNIC





LIKE THE DISTINCTLY LIGHT WINES OF ITS APPELLATION, CHABLIS PLANKS ARE A TESTAMENT TO THE POWER OF SIMPLICITY. THEIR SANDED SURFACE AND ARTFUL SHADE VARIATIONS TRANSPORT YOU TO THE SUN-WASHED CHÂTEAUX OF MARGAUX, WHERE THE NATURAL FLAVOURS OF LIFE ARE CELEBRATED. CRAFTED FROM GENUINE FRENCH OAK, MIXED GREY AND WHITE TONES CREATE A FLOWING LOOK ON CHABLIS' EFFORTLESSLY REFINED SURFACE.

SPECIFICATIONS

MANUFACTURED: MADE IN CANADA

WOOD ORIGIN: FRANCE

WOOD SPECIES: GENUINE FRENCH OAK

TYPE: ENGINEERED

GRADE: AVAILABLE IN CHARACTER OR SELECT

SHADE: LIGHT SURFACE: SANDED

EDGES: MICROBEVELLED (PLANK - LONG SIDES ONLY)

THICKNESS: 20 MM (3/4") *TOP LAYER THICKNESS IS MEASURED

BEFORE THE FINISHING PROCESS. PROCESSES SUCH AS PLANING WILL AFFECT THE OVERALL

THICKNESS.

CONSTRUCTION: PURECRAFT 3-LAYER
FINISH: HARDWAX OIL (UV CURED)

PLANK WIDTHS: 178 MM / 229 MM / 280 MM (7" / 9" / 11)

PLANK LENGTHS: 1750 MM - 2350 MM (69" - 93") **NOMINAL LENGTHS MEASURED PRIOR TO FINISHING.

AVERAGE LENGTHS ARE 6-7'.

HERRINGBONE DIMENSIONS: 101.6 MM X 508 MM (4" X 20")

CHEVRON DIMENSIONS: 101.6 MM X 406.4 MM (4" X 16")

COLOUR VARIATION: V2 - MODERATE VARIATION

CERTIFICATIONS:







FSC© AVAILABLE UPON REQUEST

CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F)

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	ASTM E 648-17 CLASS II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA

INSTALLATION

TYPE

RECOMMENDATION

Full Glue Down

Nail Down

Nail Down

Floating

Over Underfloor Heating

RECOMMENDATION

YES - RECOMMENDED

YES - WITH GLUE ASSIST

NOT RECOMMENDED

YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.