

DOVER XL

STUDIO RESERVE

Northern
WIDE PLANK



EXPERIENCE THE ALLURE OF DOVER—AN EXQUISITE PRODUCT INSPIRED BY THE BREATHTAKING CLIFFS OF THE ENGLISH SHORE. WITH COOL UNDERTONES AND DELICATE WHITE SHADES, DOVER EUROPEAN OAK ENGINEERED WIDE PLANKS CAPTURE THE ESSENCE OF THE MESMERIZING SEASIDE LANDSCAPE. COMBINING NATURAL ELEGANCE WITH A CONTEMPORARY AESTHETIC, 'DOVER' BRINGS A REFRESHING ATMOSPHERE TO ANY SPACE.

SPECIFICATIONS

MANUFACTURED:	MADE IN EUROPE
WOOD ORIGIN:	EUROPE
WOOD SPECIES:	EUROPEAN OAK
TYPE:	ENGINEERED
GRADE:	CHARACTER
SHADE:	LIGHT
SURFACE:	PLANED
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	21 MM (3/4")* WITH 6 MM WEAR LAYER.
CONSTRUCTION:	WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	330 MM - 480 MM (13" - 18.9")
PLANK LENGTHS:	1525 MM - 3658 MM (60" - 144")
COLOUR VARIATION:	V2 - MODERATE VARIATION

CERTIFICATIONS:



CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F)

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS

Reaction to fire

Emission of Formaldehyde

Janka Hardness Rating

Post Consumer Recycled Content %

PERFORMANCE

ASTM E 648-17 Class II

E1 / CARB 2 compliant

1,360 lbf (6,000 N)

NA

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	YES - RECOMMENDED
Nail Down	YES - WITH GLUE ASSIST
Floating	NOT RECOMMENDED
Over Underfloor Heating	YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors

5930 LLOYDTOWN-AURORA ROAD, SCHOMBERG ON L0G 1T0 CANADA
NORTHERNWIDEPLANK.CA 877/763/6169

Date: Apr 1, 2024