MEUSE

TANNIC





THE ANCIENT MEUSE RIVER IS AN UNIMPEDED AND ELEGANT FORCE; THIS BALANCE OF STRENGTH AND FLOW IS THE COMMON THREAD WHICH GIVES MEUSE WIDE PLANK ITS NAME—ITS NATURAL LIGHT GREY AND WHITE TONALITY REMINISCENT OF DRIFTWOOD FOUND ALONG RIVERBEDS. MADE FROM GENUINE FRENCH OAK, MEUSE IS A CULMINATION OF BOTH HISTORY AND PROGRESS, EXPERTLY BALANCED FOR A TIMELESS RESULT.

SPECIFICATIONS

MANUFACTURED: MADE IN CANADA

WOOD ORIGIN: FRANCE

WOOD SPECIES: GENUINE FRENCH OAK

TYPE: ENGINEERED

GRADE: AVAILABLE IN CHARACTER OR SELECT

SHADE: LIGHT SURFACE: SANDED

EDGES: MICROBEVELLED (PLANK - LONG SIDES ONLY)

THICKNESS: 20 MM (3/4") *TOP LAYER THICKNESS IS MEASURED

BEFORE THE FINISHING PROCESS. PROCESSES SUCH AS PLANING WILL AFFECT THE OVERALL

THICKNESS.

CONSTRUCTION: PURECRAFT 3-LAYER
FINISH: HARDWAX OIL (UV CURED)

PLANK WIDTHS: 178 MM / 229 MM / 280 MM (7" / 9" / 11)
PLANK LENGTHS: 1750 MM - 2350 MM (69" - 93") **NOMINAL

LENGTHS MEASURED PRIOR TO FINISHING. AVERAGE LENGTHS ARE 6-7'.

HERRINGBONE DIMENSIONS: 101.6 MM X 508 MM (4" X 20")

CHEVRON DIMENSIONS: 101.6 MM X 406.4 MM (4" X 16")

COLOUR VARIATION: V2 - MODERATE VARIATION

CERTIFICATIONS:







FSC© AVAILABLE UPON REQUEST

CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F)

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	ASTM E 648-17 CLASS II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA

INSTALLATION

TYPE

RECOMMENDATION

Full Glue Down

Nail Down

Nail Down

Floating

Over Underfloor Heating

RECOMMENDED

YES - RECOMMENDED

YES - WITH GLUE ASSIST

NOT RECOMMENDED

YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.