


RAINIER XL

STUDIO RESERVE

Northern
WIDE PLANK



VOLATILE, VOLCANIC, AND WORTHY OF ITS OWN NATIONAL PARK, MOUNT RAINIER HAS A FLAIR FOR THE DRAMATIC. MATCHED ONLY BY THESE RUSTIC HARDWOODS, EACH PLANK IS TREATED WITH BLACK OIL, THEN HAND-SANDED TO UNDERSCORE THEIR NATURAL AND ARTFULLY MILLED IMPERFECTIONS. AT HOME IN CHALETs AND LODGE SETTINGS, RAINIER IS WHERE RUSTIC MEETS DYNAMIC.

SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA
WOOD ORIGIN:	NORTH EASTERN/CENTRAL USA
WOOD SPECIES:	WHITE OAK
TYPE:	ENGINEERED
GRADE:	CHARACTER
SHADE:	DARK
SURFACE:	SHRUNK
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	20 MM (3/4")* WITH 6 MM WEAR LAYER.
CONSTRUCTION:	PURECRAFT 3-LAYER
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	330 MM - 381 MM (13" - 15")
PLANK LENGTHS:	1525 MM - 3658 MM (60" - 144")
COLOUR VARIATION:	V2 - MODERATE VARIATION

CERTIFICATIONS:



Declare.

FSC® AVAILABLE UPON REQUEST

CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F)

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	ASTM E 648-17 Class II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	YES - RECOMMENDED
Nail Down	YES - WITH GLUE ASSIST
Floating	NOT RECOMMENDED
Over Underfloor Heating	YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors

5930 LLOYDTOWN-AURORA ROAD, SCHOMBERG ON L0G 1T0 CANADA
NORTHERNWIDEPLANK.CA 877/763/6169

Date: Apr 3, 2024