SANTENAY

Northern WIDE PLANK

TANNIC



AUTHENTICITY PERMEATES BOTH SANTENAY WIDE PLANK AND THE REGION FROM WHICH ITS NAME DERIVES; CHARACTERIZED BY A LIGHT, NATURAL FINISH, THESE GENUINE FRENCH OAK PLANKS ARE A TRIBUTE TO THE UNDERSTATED BEAUTY OF THE EVERYDAY. LIKE THE RUSTIC STYLE THAT THIS WINE REGION IS KNOWN FOR, SANTENAY INVITES YOU TO SIT AND RELAX WITH ITS FAMILIAR WARMTH.

SPECIFICATIONS

MANUFACTURED: WOOD ORIGIN: WOOD SPECIES: TYPE: GRADE: SHADE: SURFACE: EDGES: THICKNESS:

CONSTRUCTION: FINISH: PLANK WIDTHS: PLANK LENGTHS:

HERRINGBONE DIMENSIONS: CHEVRON DIMENSIONS: COLOUR VARIATION: CERTIFICATIONS:

FSC

FSC© AVAILABLE UPON REQUEST



MADE IN CANADA FRANCE GENUINE FRENCH OAK ENGINEERED AVAILABLE IN CHARACTER OR SELECT LIGHT SANDED MICROBEVELLED (PLANK - LONG SIDES ONLY) 20 MM (3/4") *TOP LAYER THICKNESS IS MEASURED BEFORE THE FINISHING PROCESS. PROCESSES SUCH AS PLANING WILL AFFECT THE OVERALL THICKNESS PURECRAFT 3-LAYER HARDWAX OIL (UV CURED) 178 MM / 229 MM / 280 MM (7" / 9" / 11) 1750 MM - 2350 MM (69" - 93") **NOMINAL LENGTHS MEASURED PRIOR TO FINISHING. AVERAGE LENGTHS ARE 6-7'. 101.6 MM X 508 MM (4" X 20") 101.6 MM X 406.4 MM (4" X 16") V2 - MODERATE VARIATION

Declare.

CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F) Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	ASTM E 648-17 CLASS II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	YES - RECOMMENDED
Nail Down	YES - WITH GLUE ASSIST
Floating	NOT RECOMMENDED
Over Underfloor Heating	YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.