

# STONEHAM XL

STUDIO RESERVE

**Northern**  
WIDE PLANK



DISCOVER THE CAPTIVATING ALLURE OF STONEHAM EUROPEAN OAK ENGINEERED HARDWOOD FLOORING, INSPIRED BY ANCIENT EUROPEAN STONE MONUMENTS LIKE STONEHENGE AND THE PARTHENON. HANDCRAFTED WITH CHARACTER, EACH PLANK EMBODIES A BEAUTIFULLY DISTRESSED SURFACE. WITH UNRIVALED PERFORMANCE EACH WIDE PLANK BRINGS AN EXTRAORDINARY LOOK AND FEEL TO YOUR SPACE. ITS LIGHT GREY-BROWN APPEARANCE, ACHIEVED THROUGH ADDITIONAL COLOUR PIGMENTS, ADDS AN ELEGANT TOUCH.

## SPECIFICATIONS

MANUFACTURED:	MADE IN EUROPE
WOOD ORIGIN:	EUROPE
WOOD SPECIES:	EUROPEAN OAK
TYPE:	ENGINEERED
GRADE:	CHARACTER
SHADE:	GREY
SURFACE:	DISTRESSED
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	21 MM (3/4")* WITH 6 MM WEAR LAYER.
CONSTRUCTION:	WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	330 MM - 480 MM (13" - 18.9")
PLANK LENGTHS:	1525 MM - 3658 MM (60" - 144")
COLOUR VARIATION:	V3 - SUBSTANTIAL VARIATION

## CERTIFICATIONS:



FSC® AVAILABLE UPON REQUEST

## CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F)

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.

## TECHNICAL PERFORMANCE

### ESSENTIAL CHARACTERISTICS

Reaction to fire

Emission of Formaldehyde

Janka Hardness Rating

Post Consumer Recycled Content %

### PERFORMANCE

ASTM E 648-17 Class II

E1 / CARB 2 compliant

1,360 lbf (6,000 N)

NA

## INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	YES - RECOMMENDED
Nail Down	YES - WITH GLUE ASSIST
Floating	NOT RECOMMENDED
Over Underfloor Heating	YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors

5930 LLOYDTOWN-AURORA ROAD, SCHOMBERG ON L0G 1T0 CANADA  
NORTHERNWIDEPLANK.CA 877/763/6169

Date: Apr 1, 2024