

STONEHAM XL

STUDIO RESERVE

Northern
WIDE PLANK



DISCOVER THE CAPTIVATING ALLURE OF STONEHAM EUROPEAN OAK ENGINEERED HARDWOOD FLOORING, INSPIRED BY ANCIENT EUROPEAN STONE MONUMENTS LIKE STONEHENGE AND THE PARTHENON. HANDCRAFTED WITH CHARACTER, EACH PLANK EMBODIES A BEAUTIFULLY DISTRESSED SURFACE. WITH UNRIVALED PERFORMANCE EACH WIDE PLANK BRINGS AN EXTRAORDINARY LOOK AND FEEL TO YOUR SPACE. ITS LIGHT GREY-BROWN APPEARANCE, ACHIEVED THROUGH ADDITIONAL COLOUR PIGMENTS, ADDS AN ELEGANT TOUCH.

SPECIFICATIONS

MANUFACTURED:	MADE IN EUROPE
WOOD ORIGIN:	EUROPE
WOOD SPECIES:	EUROPEAN OAK
TYPE:	ENGINEERED
GRADE:	CHARACTER
SHADE:	GREY
SURFACE:	DISTRESSED
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	21 MM (3/4")* WITH 6 MM WEAR LAYER.
CONSTRUCTION:	WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	330 MM - 480 MM (13" - 18.9")
PLANK LENGTHS:	1525 MM - 3658 MM (60" - 144")
COLOUR VARIATION:	V3 - SUBSTANTIAL VARIATION

CERTIFICATIONS:



CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F)

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	ASTM E 648-17 Class II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	YES - RECOMMENDED
Nail Down	YES - WITH GLUE ASSIST
Floating	NOT RECOMMENDED
Over Underfloor Heating	YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors

5930 LLOYDTOWN-AURORA ROAD, SCHOMBERG ON L0G 1T0 CANADA
NORTHERNWIDEPLANK.CA 877/763/6169

Date: Apr 1, 2024