OAR ARTIFAX COLLECTION





INSPIRED BY THE ORGANIC CHARM OF CANOE PADDLES, OAR CAPTURES THE ESSENCE OF A COZY CABIN-LIKE AMBIANCE WITH ITS INVITING AESTHETIC. ITS UNIQUE GRAIN AND WAGON WHEEL KNOTS ARE BRUSHED TO BRING OUT THE NATURAL LOOK OF THE WOOD, RESULTING IN AN ENDURING CHARACTER WITH AN ARRAY OF HUES FROM AMBER TO DEEP MALT BROWN. OAR INFUSES YOUR SPACE WITH A TOUCH OF HERITAGE AND IRRESISTIBLE CHARM.

SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA		
WOOD ORIGIN:	EASTERN/CENTRAL USA - OLD BARNS/BUILDINGS		
WOOD SPECIES:	RECLAIMED HEMLOCK		
TYPE:	ENGINEERED		
GRADE:	GENUINE RECLAIMED		
SHADE:	NATURAL		
SURFACE:	BRUSHED		
EDGES:	EASED (PLANK - LONG SIDE ONLY)		
THICKNESS:	20 MM (3/4") WITH 6 MM WEAR LAYER*TOP LAYER		
	THICKNESS IS MEASURED BEFORE THE FINISHING		
	PROCESS. PROCESSES SUCH AS PLANING WILL		
	AFFECT THE OVERALL THICKNESS.		
CONSTRUCTION:	PURECRAFT 3-LAYER OR		
	WBP BALTIC BIRCH PLYWOOD		
FINISH:	HARDWAX OIL (UV CURED)		
PLANK WIDTHS:	102 MM - 203 MM (4" - 8") RANDOM WIDTHS**MAY		
	RECEIVE WIDER WIDTHS. BASED ON AVAILABILITY.		
PLANK LENGTHS:	914 MM - 3581 MM (36" - 141")***LENGTHS ARE		
	NOMINAL AND MAY CONTAIN UP TO 5% SHORTER		
	THAN MINIMUM LENGTH		
HERRINGBONE DIMENSIONS:	4" X 20" (101.6 MM X 508 MM)		
CHEVRON DIMENSIONS:	4" X 16" (101.6 MM X 406.4 MM)		
COLOUR VARIATION:	V3 - SUBSTANTIAL VARIATION		
CERTIFICATIONS:			
\sim	<u> </u>		

CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F) Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS

Post Consumer Recycled Content %

Emission of Formaldehyde Janka Hardness Rating

		-	
	MAS		
	N,		
-	1	1	
r indo	or condition		



The mark of



FSC© AVAILABLE UPON REQUEST		
	PERFORMANCE	
	ASTM E 648-17 CLASS II	
	E1 / CARB 2 COMPLIANT	
	1,360 LBF (6,000 N)	
	25	

INSTALLATION

Reaction to fire

TYPE	RECOMMENDATION
Full Glue Down	YES - RECOMMENDED
Nail Down	YES - WITH GLUE ASSIST
Floating	NOT RECOMMENDED
Over Underfloor Heating	YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.