PALOMAR

ICONIC COLLECTION





INSPIRED BY THE ENERGY OF THE PENINSULAR MOUNTAINS IN NORTHERN SAN DIEGO, PALOMAR IS MADE FOR THOSE WHO CRAVE AN EARTHY, RUGGED EXPRESSION OF CALIFORNIA CHARM. SANDED BY HAND, BLEACHED AND BRUSHED WITH CARE, EACH PLANK FEELS GRACIOUSLY AGED AND WARM. WHETHER A TRADITIONAL OR MID-CENTURY DESIGN, PALOMAR IS ENDLESSLY VERSATILE AND UNDENIABLY COZY.

SPECIFICATIONS

MANUFACTURED: MADE IN CANADA

WOOD ORIGIN: NORTH EASTERN/CENTRAL USA

WOOD SPECIES: WHITE OAK
TYPE: ENGINEERED
GRADE: CHARACTER
SHADE: LIGHT
SURFACE: SHRUNK

EDGES: MICROBEVELLED (PLANK - LONG SIDES ONLY)

THICKNESS: 20 MM (3/4")

CONSTRUCTION: WBP BALTIC BIRCH PLYWOOD
FINISH: HARDWAX OIL (UV CURED)
PLANK WIDTHS: 229 MM / 280 MM (9" / 11")
PLANK LENGTHS: 914 MM - 3581 MM (36" - 141")**
**WITH SOME NESTED LENGTHS

HERRINGBONE DIMENSIONS: 101.6 MM X 508 MM (4" X 20")

CHEVRON DIMENSIONS: 101.6 MM X 406.4 MM (4" X 16")

COLOUR VARIATION: V2 - MODERATE VARIATION

CERTIFICATIONS:







FSC© AVAILABLE UPON REQUEST

CLEANING AND CARE

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors.

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	ASTM E 648-17 Class II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA

INSTALLATION

TYPE

RECOMMENDATION

Full Glue Down

Yes - Recommended

Nail Down

Yes - With Glue Assist

Floating

Not Recommended

Over Underfloor Heating

Yes - Refer to NWP Radiant Heat Guide

*APPLICATIONS:

Floors, Walls and Ceilings. Stair Treads and Vents Also Available