

# RIVER BED

ARTIFAX COLLECTION

**Northern**  
WIDE PLANK



MILL CREEK IS LIGHTLY SKIP PLANED BY OUR CRAFTSMEN, TO PRESERVE THE ORIGINAL CHARACTER FOR GENERATIONS TO COME.

## SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA
WOOD ORIGIN:	EASTERN/CENTRAL USA – OLD BARNs/BUILDINGS
WOOD SPECIES:	RECLAIMED OAK
TYPE:	ENGINEERED
GRADE:	GENUINE RECLAIMED
SHADE:	BROWN
SURFACE:	BRUSHED
EDGES:	EASED (PLANK - LONG SIDE ONLY)
THICKNESS:	20 MM (3/4") WITH 6 MM WEAR LAYER*TOP LAYER THICKNESS IS MEASURED BEFORE THE FINISHING PROCESS. PROCESSES SUCH AS PLANING WILL AFFECT THE OVERALL THICKNESS.
CONSTRUCTION:	PURECRAFT 3-LAYER OR WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	102 MM - 203 MM (4" - 8") RANDOM WIDTHS**MAY RECEIVE WIDER WIDTHS. BASED ON AVAILABILITY.
PLANK LENGTHS:	914 MM - 3581 MM (36" - 141")***LENGTHS ARE NOMINAL AND MAY CONTAIN UP TO 5% SHORTER THAN MINIMUM LENGTH..
HERRINGBONE DIMENSIONS:	4" X 20" (101.6 MM X 508 MM)
CHEVRON DIMENSIONS:	4" X 16" (101.6 MM X 406.4 MM)
COLOUR VARIATION:	V3 - SUBSTANTIAL VARIATION
CERTIFICATIONS:	

## CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F) Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.



FSC® AVAILABLE UPON REQUEST

## TECHNICAL PERFORMANCE

### ESSENTIAL CHARACTERISTICS

Reaction to fire  
Emission of Formaldehyde  
Janka Hardness Rating  
Post Consumer Recycled Content %

### PERFORMANCE

ASTM E 648-17 CLASS II  
E1 / CARB 2 COMPLIANT  
1,360 LBF (6,000 N)  
25

## INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	YES - RECOMMENDED
Nail Down	YES - WITH GLUE ASSIST
Floating	NOT RECOMMENDED
Over Underfloor Heating	YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.

5930 LLOYDTOWN-AURORA ROAD, SCHOMBERG ON L0G 1T0 CANADA  
NORTHERNWIDEPLANK.CA 877/763/6169

Date: Mar 7, 2024