SMOKEHOUSE



ARTIFAX COLLECTION



SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA
WOOD ORIGIN:	ONTARIO
WOOD SPECIES:	RECLAIMED HEMLOCK
TYPE:	ENGINEERED
GRADE:	GENUINE RECLAIMED
SHADE:	DARK
SURFACE:	FOUNDRY
EDGES:	EASED (PLANK - LONG SIDE ONLY)
THICKNESS:	20 MM (3/4") WITH 6 MM WEAR LAYER*TOP LAYER
	THICKNESS IS MEASURED BEFORE THE FINISHING
	PROCESS. PROCESSES SUCH AS PLANING WILL
	AFFECT THE OVERALL THICKNESS.
CONSTRUCTION:	PURECRAFT 3-LAYER OR
	WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	102 MM - 229 MM (4" - 9") RANDOM WIDTH**MAY
	RECEIVE WIDER WIDTHS. BASED ON AVAILABILITY.
PLANK LENGTHS:	914 MM - 3581 MM (36" - 141")***LENGTHS ARE
	NOMINAL AND MAY CONTAIN UP TO 5% SHORTER
	THAN MINIMUM LENGTH
HERRINGBONE DIMENSIONS:	4" X 20" (101.6 MM X 508 MM)
CHEVRON DIMENSIONS:	4" X 16" (101.6 MM X 406.4 MM)
COLOUR VARIATION:	V3 - SUBSTANTIAL VARIATION
CERTIFICATIONS:	

CLEANING AND CARE

Northern Wide Plank requires a relative humidity range of minimum 30%, maximum 65%, and a temperature range between 15°C (60°F) to 24°C (75°F) Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors for more info.

TECHNICAL PERFORMANCE

FSC© AVAILABLE UPON REQUEST

FSC

The mark of



ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	ASTM E 648-17 CLASS II
Emission of Formaldehyde	E1 / CARB 2 COMPLIANT
Janka Hardness Rating	1,360 LBF (6,000 N)
Post Consumer Recycled Content %	25

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	YES - RECOMMENDED
Nail Down	YES - WITH GLUE ASSIST
Floating	NOT RECOMMENDED
Over Underfloor Heating	YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.