# SOLSTICE

### **ICONIC**





INSPIRED BY THOSE MOMENTS IN THE YEAR WHEN THE SUN APPEARS TO STAND STILL, SOLSTICE HAS AN APPROPRIATELY LIGHT AND AIRY PALETTE. EACH PLANK'S HONEY-BROWN TONE IS MUTED BY SOFT WHITE OILS AND FINISHED WITH A HAND-SANDED, WIRE-BRUSHED TEXTURE. THE EFFECT IS SOPHISTICATED AND DAZZLING IN SETTINGS RANGING FROM SCANDINAVIAN TO MID-CENTURY.

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors.

## **SPECIFICATIONS**

MANUFACTURED: MADE IN CANADA

WOOD ORIGIN: NORTH EASTERN/CENTRAL USA

WOOD SPECIES: WHITE OAK
TYPE: ENGINEERED

GRADE: AVAILABLE IN CHARACTER OR SELECT

SHADE: LIGHT SURFACE: BRUSHED

EDGES: MICROBEVELLED (PLANK - LONG SIDES ONLY)

THICKNESS: 20 MM (3/4") WITH 6 MM WEAR LAYER\*TOP LAYER

THICKNESS IS MEASURED BEFORE THE FINISHING

PROCESS. PROCESSES SUCH AS PLANING WILL

AFFECT THE OVERALL THICKNESS.

CONSTRUCTION: WBP BALTIC BIRCH PLYWOOD

FINISH: HARDWAX OIL (UV CURED)

PLANK WIDTHS: 178 mm / 229 mm / 280 mm (7" / 9" / 11")

PLANK LENGTHS: 914 MM - 3581 MM (36" - 141")\*\*NOMINAL LENGTHS

MEASURED PRIOR TO FINISHING. AVERAGE

LENGTHS ARE 6'-7'.

HERRINGBONE DIMENSIONS: 4" X 20" (101.6 MM X 508 MM)

CHEVRON DIMENSIONS: 4" X 16" (101.6 MM X 406.4 MM)

COLOUR VARIATION: V2 - MODERATE VARIATION

CERTIFICATIONS:





FSC© AVAILABLE UPON REQUEST



# TECHNICAL PERFORMANCE

**CLEANING AND CARE** 

ESSENTIAL CHARACTERISTICS

Reaction to fire

ASTM E 648-17 Class II

Emission of Formaldehyde

En / CARB 2 compliant

Janka Hardness Rating

1,360 lbf (6,000 N)

Post Consumer Recycled Content %

NA

#### **INSTALLATION**

TYPE

RECOMMENDATION

Full Glue Down

Nail Down

Nail Down

Floating

Over Underfloor Heating

RECOMMENDATION

YES - RECOMMENDED

YES - WITH GLUE ASSIST

NOT RECOMMENDED

YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.