

VENTURA

ICONIC

Northern
WIDE PLANK



TOURISTS HAVE BEEN CHARMED BY VENTURA SINCE THE SPANISH FOUNDED IT IN 1782. REMINISCENT OF THE SEAPORT, EACH VENTURA PLANK IS HAND-SANDED, HARD WAX-OILED, BRUSHED, AND BLEACHED TO ACHIEVE A RELAXED, COASTAL APPEARANCE. SUBTLE GRAINS AND VARIATIONS ARE UNIQUE YET TRADITIONAL, TURNING ANY SPACE INTO A REASON TO GATHER.

SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA
WOOD ORIGIN:	NORTH EASTERN/CENTRAL USA
WOOD SPECIES:	WHITE OAK
TYPE:	ENGINEERED
GRADE:	CHARACTER
SHADE:	LIGHT
SURFACE:	SHRUNK
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)
THICKNESS:	20 MM (3/4") WITH 6 MM WEAR LAYER*TOP LAYER THICKNESS IS MEASURED BEFORE THE FINISHING PROCESS. PROCESSES SUCH AS PLANING WILL AFFECT THE OVERALL THICKNESS.
CONSTRUCTION:	WBP BALTIC BIRCH PLYWOOD
FINISH:	HARDWAX OIL (UV CURED)
PLANK WIDTHS:	229 mm / 280 mm (9" / 11")
PLANK LENGTHS:	914 MM - 3581 MM (36" - 141")**NOMINAL LENGTHS MEASURED PRIOR TO FINISHING. AVERAGE LENGTHS ARE 6'-7'.
HERRINGBONE DIMENSIONS:	4" X 20" (101.6 MM X 508 MM)
CHEVRON DIMENSIONS:	4" X 16" (101.6 MM X 406.4 MM)
COLOUR VARIATION:	V2 - MODERATE VARIATION
CERTIFICATIONS:	

CLEANING AND CARE

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors.

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS

Reaction to fire
Emission of Formaldehyde
Janka Hardness Rating
Post Consumer Recycled Content %

PERFORMANCE

ASTM E 648-17 Class II
E1 / CARB 2 compliant
1,360 lbf (6,000 N)
NA

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	YES - RECOMMENDED
Nail Down	YES - WITH GLUE ASSIST
Floating	NOT RECOMMENDED
Over Underfloor Heating	YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.



The mark of responsible forestry

FSC® AVAILABLE UPON REQUEST

Declare.