WHITESTONE

Northern WIDE PLANK

ICONIC



LIGHT WASHED TONES MIXED WITH GREY UNDERTONES PERFECT THE CONTEMPORARY SETTING.

SPECIFICATIONS

MANUFACTURED:	MADE IN CANADA	
WOOD ORIGIN:	NORTH EASTERN/CENTRAL USA	
WOOD SPECIES:	WHITE OAK	
TYPE:	ENGINEERED	
GRADE:	AVAILABLE IN CHARACTER OR SELECT	
SHADE:	GREY	
SURFACE:	SANDED	
EDGES:	MICROBEVELLED (PLANK - LONG SIDES ONLY)	
THICKNESS:	20 MM (3/4") WITH 6 MM WEAR LAYER*TOP LAYER	
	THICKNESS IS MEASURED BEFORE THE FINISHING	
	PROCESS. PROCESSES SUCH AS PLANING WILL	
	AFFECT THE OVERALL THICKNESS.	
CONSTRUCTION:	WBP BALTIC BIRCH PLYWOOD	
FINISH:	HARDWAX OIL (UV CURED)	
PLANK WIDTHS:	178 mm / 229 mm / 280 mm (7" / 9" / 11")	
PLANK LENGTHS:	914 MM - 3581 MM (36" - 141")**NOMINAL LENGTHS	
	MEASURED PRIOR TO FINISHING. AVERAGE	
	LENGTHS ARE 6'-7'.	
HERRINGBONE DIMENSIONS:	4" X 20" (101.6 MM X 508 MM)	
CHEVRON DIMENSIONS:	4" X 16" (101.6 MM X 406.4 MM)	
COLOUR VARIATION:	V3 - SUBSTANTIAL VARIATION	
CERTIFICATIONS:		





FSC© AVAILABLE UPON REQUEST

Declare.

CLEANING AND CARE

Refer to NWP Cleaning & Care for Hardwax Oil finished wood floors.

TECHNICAL PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	ASTM E 648-17 Class II
Emission of Formaldehyde	E1 / CARB 2 compliant
Janka Hardness Rating	1,360 lbf (6,000 N)
Post Consumer Recycled Content %	NA

INSTALLATION

TYPE	RECOMMENDATION
Full Glue Down	YES - RECOMMENDED
Nail Down	YES - WITH GLUE ASSIST
Floating	NOT RECOMMENDED
Over Underfloor Heating	YES - REFER TO NWP RADIANT HEAT GUIDE

APPLICATIONS: Floors, Walls and Ceilings. Stair Treads, Nosing, and Vents are also Available.