innovate...laminate



Peak professional is a reliable, functional and stylish range of systems for efficiently producing high quality lamination



Design

The professional series offers style, reliability and efficiency for laminating a multitude of documents. This unique range has been developed to give you the expert results you need quickly and easily.

Function

Designed to fit practically into any busy working environment, this range combines durability with user friendly appeal and a modern appearance.

Efficiency

Efficiency and performance have been key objectives in the design of this range. Four hot rollers and quick warm up time make laminating with these systems hassle free.

Reliability

This range uses high quality components including metal gears, larger rollers and bigger motors. Each system is easy to use and does not require training.



Cooling Tem

Temperature Control





Technology

Mode

IDEAL FOR LAMINATING

- ID and business cards
- signs & notices
- glossy photographs
- posters
- certificates

GREAT FOR USE IN

- offices
- local government
- education schools, colleges and universities

PEAK Professional series

PEAK PP-260 / PP-330 / PP-450

PP-260

- · laminates from ID to A4
- hot roller technology
- variable temperature control
- laminates both hot and cold
- anti-jam reverse mode
- bubble free photo lamination
- power light indicator
- · ready light indicator
- no card carrier required*



PP-330

- laminates from ID to A3
- hot roller technology
- · variable temperature control
- · laminates both hot and cold
- · anti-jam reverse mode
- · bubble free photo lamination
- · power light indicator
- ready light indicator
- · no card carrier required*





PP-450

- · laminates from ID to A2
- hot roller technology
- · variable temperature control
- · laminates both hot and cold
- · anti-jam reverse mode
- bubble free photo lamination
- power light indicator
- · ready light indicator
- no card carrier required*



* A card carrier or Lifejacket IS required if the document does not fully match the size of the pouch or if you are laminating small odd shaped pieces. Please ask for more details.



PEAK PP-330

specifications	PP-260 (A4)	PP-330 (A3)	PP-450 (A2 - not shown)	
approx laminating speed (mm/min)	560	560	690	
maximum width (mm)	260	320	450	
laminating thickness (micron)	360	360	360	
warm-up time (mins)	5	5	5	
laminating temperature (°C)	100-160	100-160	100-160	
power supply AC (V–Hz)	220/240 (50-60)	220/240 (50-60)	220/240 (50-60)	
power consumption (W)	360	450	650	
dimensions without packaging (mm)	440x200x110	500x200x110	630x200x110	
weight without packaging (Kg)	7	8	10	
warranty (year)	2	2	2	
number of rollers	4	4	4	



01908 563149 sales@chilvers.co.uk www.chilvers.co.uk