



Hydraulic Hinge-Closer Selection Guide



MODEL	CODE	MODEL	PRODUCT DESCRIPTION	MOUNTING TYPE	FIXING METHOD	MAX OPENING ANGLE	SELF-CLOSING FROM	
READYFIT™	74108333T	RF108S S 180	Safety Hinge/Closer	External	Alum Screw-on	180°	180°	
	74108323T	RF108SF S	Safety Hinge/Closer	External	Alum Screw-on	88°	88°	
	74108313T	RF108 S	Hinge/Closer	External	Alum Screw-on	178°	83°	
	74001313T	RFSM S	Hinge Only	External	Alum Screw-on	178°	N/A	
	74108335T	RF108S W 180	Safety Hinge/Closer	External	Steel Weld-on	180°	180°	
	74108325T	RF108SF W	Safety Hinge/Closer	External	Steel Weld-on	88°	88°	
	74108315T	RF108 W	Hinge/Closer	External	Steel Weld-on	178°	83°	
	74001315T	RFSM W	Hinge Only	External	Steel Weld-on	178°	N/A	
FLUSH MOUNT	75001213	SMAT90 S	Hinge Only	Flush	Alum Screw-on	180°	N/A	
	75057213M	57AT90 S	Hinge/Closer	Flush	Alum Screw-on	180°	85°	
	75057223M	57SFAT980 S	Hinge/Closer	Flush	Alum Screw-on	90°	90°	
	75108213M	108AT90 S	Safety Hinge/Closer	Flush	Alum Screw-on	180°	85°	
	75108223M	108SF AT90 S	Safety Hinge/Closer	Flush	Alum Screw-on	90°	90°	
	75001214	SMAT90 W	Hinge Only	Flush	Steel Weld-on	180°	N/A	
	75057214M	57AT90 W	Hinge/Closer	Flush	Steel Weld-on	180°	85°	
	75057224M	57SF AT90 W	Hinge/Closer	Flush	Steel Weld-on	90°	90°	
	75108214M	108 AT90 W	Hinge/Closer	Flush	Steel Weld-on	180°	85°	
	75108224M	108SFAT90 W	Safety Hinge/Closer	Flush	Steel Weld-on	90°	90°	
	CENTER MOUNT	75001113	SM S	Heavy-Duty Hinge	Center	Alum Screw-on	90°	N/A
		75057113M	57 S	Hinge/Closer	Center	Alum Screw-on	90°	85°
75057123M		57SF S	Hinge/Closer	Center	Alum Screw-on	90°	90°	
75108113M		108 S	Safety Hinge/Closer	Center	Alum Screw-on	90°	85°	
75108123M		108SF S	Safety Hinge/Closer	Center	Alum Screw-on	90°	90°	
75001114		SM W	Heavy-Duty Hinge	Center	Steel Weld-on	90°	N/A	
75057114M		57 W	Hinge/Closer	Center	Steel Weld-on	90°	85°	
75057124M		57SF W	Hinge/Closer	Center	Steel Weld-on	90°	90°	
75108114M		108 W	Safety Hinge/Close	Center	Steel Weld-on	90°	85°	
75108124		108SF W	Safety Hinge/Close	Center	Steel Weld-on	90°	90°	
EASY™	72108423	SC108SF S	Hydraulic Closer	External	Alum Screw-on	90°	90°	
CONCEALFIT™	77108523	SC CF KIT	Door Closer/Hinge Kit	Center	Alum Screw-on	125°	125°	
	78108513	SC CF HINGE	Plain Pivot Door Hinge	Center	Alum Screw-on	125°	N/A	

Post Mounting Brackets (sold separately)



HORIZONTAL GAP VARIANCE	MINIMUM POST/DOOR SIZE	FIXING BRACKET CODE	SELF-CLOSING SAFETY/ POOL	ADA COMPLIANT	SELF-CLOSING WITH HOLD OPEN	NON SELF-CLOSING	ADJUSTABLE CLOSING SPEED	FINAL SNAP ACTION
½"-1¾" (12-35mm)	2" (50mm)	Included	*●	●			●	●
½"-1¾" (12-35mm)	2" (50mm)	Included	*●				●	●
½"-1¾" (12-35mm)	2" (50mm)	Included		●	●		●	●
½"-1¾" (12-35mm)	2" (50mm)	Included				●		
½"-1¾" (12-35mm)	2" (50mm)	Included	*●	●			●	●
½"-1¾" (12-35mm)	2" (50mm)	Included	*●	●			●	●
½"-1¾" (12-35mm)	2" (50mm)	Included						
½"-1¾" (12-35mm)	2" (50mm)	Included						
½" (13mm)	2" (50mm)	7515				●		
½" (13mm)	2" (50mm)	7515		●	●		●	
½" (13mm)	2" (50mm)	7515	*●				●	
½" (13mm)	3" (76mm)	7515		●	●		●	●
½" (13mm)	3" (76mm)	7515	*●				●	●
½" (13mm)	2" (50mm)	7525				●		
½" (13mm)	2" (50mm)	7525		●	●		●	
½" (13mm)	2" (50mm)	7525	*●				●	
½" (13mm)	3" (76mm)	7525		●	●		●	●
½" (13mm)	3" (76mm)	7525	*●				●	●
2½"-3" (63-76mm)	2½" (64mm)	7511, 7512, 7513				●		
2½"-3" (63-76mm)	2½" (64mm)	7511, 7512, 7513		●	●		●	
2½"-3" (63-76mm)	2½" (64mm)	7511, 7512, 7513	*●				●	
2½"-3" (63-76mm)	3" (76mm)	7511, 7512, 7513		●	●		●	●
2½"-3" (63-76mm)	3" (76mm)	7511, 7512, 7513	*●				●	●
2½"-3" (63-76mm)	2½" (64mm)	7526				●		
2½"-3" (63-76mm)	2½" (64mm)	7526		●	●		●	
2½"-3" (63-76mm)	2½" (64mm)	7526	*●				●	
2½"-3" (63-76mm)	3" (76mm)	7526		●	●		●	●
2½"-3" (63-76mm)	3" (76mm)	7526	*●				●	●
2-4" (51-102mm)	2" (50mm)	Included	*●				●	●
N/A	1.6" (40mm)	N/A		●			●	●
N/A	1.6" (40mm)	N/A						

*Check local pool barrier guidelines for proper installation methods. (SF) = Gate will not hold open at 90° (OK for safety gates). Do NOT use a hinge with a 90° hold-open feature for pool/child safety gates. Hinges must be at least 36" (900mm) apart so that they cannot be used as footholds by toddlers. CAUTION: A gate-stop must be installed when using SF models. Gate must not be allowed to open past 90°. Doing so voids warranty.