

White Woven UV Resistant Ground Cover Fabric

Series: FAB-WUVR

Recommended Applications: Ground Cover

Property	Test Method	Unit	Minimum Average
Material			Polypropylene
Color			White with Black Stripe Every 12"
Construction Weave	ASTM D-5261	OZ/SY (GSM)	3.2 (108)
Grab Tensile	ASTM D-4632	LBS	Warp 175 Weft 100
Grab Elongation	ASTM D-4632	%	Warp 25 Weft 22
Trapezoid Tear	ASTM-4533	LBS	Warp 80 Weft 70
Puncture	ASTM D-6241	LBS	500
Water Permeability	ASTM D-4491	GAL/MIN/SF	15
Ultraviolet Exposure	ASTM D-4355	% Strength Retained	70% After 2500 Hrs. Xenon Arc Exposure

To the best of our knowledge, the information contained herein is accurate. However, Pro Fabric Supply cannot anticipate all conditions under which the above product information and the products which we distribute or the products of other distributors or manufacturers in combination with the products which we offer, may be used. We accept no responsibility for results obtained by the application of this information or the safety or suitability of the products we distribute either alone or in combination with other products. Final determination of the suitability of any information or material for the used contemplated, or its manner of use, and whether the suggested use infringes any patents is the sole responsibility of the user.

Please note: Pro Fabric Supply is a distributor of geotextile fabric, not the manufacturer. We source material from a number of different United States based geotextile manufacturers.