

# 746PSA

6.5 MIL INKJET MATTE PAPER WITH  
PRESSURE SENSITIVE ADHESIVE

## PRINTER COMPATIBILITY



\*For additional information visit [www.dietzgen.com](http://www.dietzgen.com)

\*Does not guarantee optimal performance

## DESCRIPTION

746PSA is 6.5 mil Inkjet coated paper featuring a smooth bright white surface and a pressure sensitive adhesive. 746PSA proprietary instant dry coating produces good print quality, line acuity and image clarity across multiple print technologies without sacrificing print speed or color accuracy. 746PSA offers plug and play printing with standard onboard "coated paper" settings on most inkjet printers.

## PHYSICAL CHARACTERISTICS

Caliper	6.5 mil (10 mil total)
Basis Weight	135 GSM
Bond Weight	36LB
Brightness	95
Opacity	98%
Finish	Matte
Whiteness	NA
Smoothness	NA
Lab Values	NA
Base material	Paper
Structure	Coated

\*All values are for reference only

## FEATURES AND BENEFITS

- Instant dry
- Good ink adhesion
- Good line acuity
- Good black density
- Smooth matte finish
- Compatible with a variety of WF inkjet printers
- Compatible with thermal and PSA overlaminates
- No off setting
- Excellent post processing and finishing

## PROCESSING TIPS

- Preferred side out

## FINISHING & PRINTING

- Compatible with pressure sensitive, heat assist and thermal overlaminates.
- Allow sufficient time for inkjet prints to completely dry before rolling, laminating or cutting.
- Use a sharp blade to prevent ink and toner flaking on the edges
- Overlamination is not required. However, it can provide additional surface protection from dirt, abrasion and moisture.

## SHELF LIFE

2 years from ship date

## STORAGE CONDITIONS

Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%

## OPTIMAL SERVICE ENVIRONMENT

Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%