

902

8 MIL POLYPROPYLENE BANNER - MATTE

DESCRIPTION

902 is an 8 mil, tear resistant, smooth, polypropylene banner with a low glare, matte finish and a water resistant, scratch resistant coating. 902 provides excellent ink adhesion, print quality, black density, color pop and image clarity as well as exceptional strength and durability for repeated handling products lay extremely flat, both on the printer and in final application. Short term outdoor.

PHYSICAL CHARACTERISTICS

Caliper	8 mil
Basis Weight	170 g/m ²
Brightness	NA
Opacity	90%
Finish	Matte
Whiteness	120
Smoothness	NA
Lab Values	NA
Base material	Polypropylene Film (PP)
Structure	Coated

*All values are for reference only

FEATURES AND BENEFITS

- Tear resistant polypropylene base
- Excellent print performance
- Excellent ink adhesion
- Excellent black density and color pop
- Water / fade / scratch resistant coating
- Smooth matte finish
- Lay flat coating
- Short term outdoor durable
- Can be grommeted and welded
- Compatible with PSA & thermal overlaminates

PRINTER COMPATIBILITY



*For additional information visit www.dietzgen.com

*Does not guarantee optimal performance

PROCESSING TIPS

- Preferred side out

FINISHING & PRINTING

- Allow sufficient time for prints to completely dry before rolling, laminating or cutting.
- Use a sharp blade to prevent ink and toner flaking on the edges
- Compatible with most brands of banner tape
- Compatible with most brands of grommets
- Grommets should be placed in multiple layers in the hemline (reinforced corners are also recommended)

SHELF LIFE

2 years from ship date

STORAGE CONDITIONS

Temperature	70° F (21° C)
Relative Humidity	50%
Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%

OPTIMAL SERVICE ENVIRONMENT

Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%