

XM1255[™]

Offering three solutions in one easy-to-use package, the XM1255 makes applying adhesive to mockups, storyboards, or comps up to 11.75" wide fast and easy.

Instantly applies laminate, adhesive or both without heat or electricity. Simply feed the item in, turn the handle, and trim. No smell, no mess, no waiting.

- Aggressive adhesive, coupled with high pressure rollers, improves both transfer and bonding quality
- Patented drop-in cartridges allow quick and easy application changes
- Even, edge-to-edge adhesive application
- Environmentally safe



As easy as 1, 2, 3



1. Insert Item



2. Turn Handle



3. Trim

XM1255™

Product Specifications

Footprint	10.5" x 13" x 15" (26.7cm x 33cm x 38.1cm)
Weight/Packed Weight	14.75lbs (6.6kg) / 18.25lbs (8.2kg)
Document Thickness (max.)	0.125" (3.2mm)
Finished Document Width (max.)	11.75" (29.8cm)
Power Requirements	None
Cutter	Removable, replaceable cutter



Product Supply Description

- **Permanent High-Tack Adhesive:** Extremely aggressive adhesive instantly creates a permanent bond on most surfaces. Sets instantly and will not peel. Acid-Free.
- **Permanent Standard Adhesive:** Moderately aggressive adhesive creates a permanent bond on most surfaces. Can be touched to surface, peeled back quickly, and replaced. Acid-Free.
- **Repositionable Adhesive:** Allows items to be repositioned over and over. Easy removal from glass, walls, paper, and most other surfaces. Acid-Free.
- **Standard Use Laminate:** High gloss film suitable for use on a variety of substrates. Superior adhesion. Compatible with most media. Acid-Free.
- **Combination — Laminate/Adhesive:** One of the laminate products described on the top surface and one of the Acid-Free adhesives described on the bottom surface. Acid-Free.

The XM1255 is your complete professional document finishing system. Instantly applies laminate, adhesive or both. Perfect for presentations, comps, packaging mock-ups, signs, displays, and short-run labels.

Part Number	Product Description	Material Length	Material Width	Laminate & Adhesive Combination Thickness (per side)	Mounting Adhesive Thickness	Adhesive pH	Mounting Adhesive Strength (1:10; 10-high)	PAT Approved
Adhesive Application Cartridges								
● AT1251-100	Permanent High-Tack	100' (30.5m)	12" (30.5cm)	N/A	0.6mil (15.2mic)	Acid-Free	10	Yes
● AT1255-100	Permanent Standard	100' (30.5m)	12" (30.5cm)	N/A	0.6mil (15.2mic)	Acid-Free	8	Yes
● AT1256-100	Repositionable	100' (30.5m)	12" (30.5cm)	N/A	1.1mil (27.9mic)	Acid-Free	3	Yes
Laminate Cartridges								
● DL1251-150	2-Sided Standard Use Laminate	150' (95.7m)	12" (30.5cm)	2.7mil (67.5mic)	N/A	Acid-Free	N/A	Yes
Combination One Side Lamination / One Side Adhesive Application								
● LAT1251-100	1 Side Standard Use Laminate 1 Side High-Tack Adhesive	100' (30.5m)	12" (30.5cm)	2.7mil (67.5mic)	0.6mil (15.2mic)	Acid-Free	10	Yes
● LAT1256-100	1 Side Standard Use Laminate 1 Side Repositionable Adhesive	100' (30.5m)	12" (30.5cm)	2.7mil (67.5mic)	1.1mil (27.9mic)	Acid-Free	3	Yes
Cutter								
2342.01	Replaceable Cutter Bar and Blade Assembly							
2343.01	Replacement Tray							

Your authorized Xyron Dealer

GS Direct Inc
1-800-234-3729
www.gsdirect.net

www.xyronpro.com | 1.800.793.3523