

Floating shelf installation

◆ LED lamp specification

Size: 80mm x 25mm

Power supply: AAA*3


Power: 0.5W

Motion sensor range: 3M/100°


Light case material: ABS+PC

◆ Product schematic

POSITIVE



BACK



◆ Battery precautions

- Each puck light uses 3AAA(4.5V) batteries.
- Always purchase the correct size and grade of battery most suitable for the intended use. Replace all batteries of a set at the same time.
- Do not mix old and new batteries. Do not mix Alkaline.
- Clean the battery contacts and also those of the device prior to battery installation.
- Ensure the batteries are installed correctly with regards to polarity (+ and -).
- Remove batteries from equipment which is not to be used for an extended period of time. Remove used batteries promptly.

Max shelf load capacity is achieved by mounting screws into studs or cement walls.

IF MOUNTING TO GYPSUM ROCK (CAVITY WALL), IT IS ADVISABLE TO MOUNT SCREWS TO A STUD OR STUDS WHERE POSSIBLE.

HOWEVER DO NOT LEAVE EITHER END OF BACKPLATE UNSUPPORTED BY AT LEAST ONE ANCHOR.

FOR HOLLOW WALL MOUNTING YOU CAN USE ANY OF THE HOLES IN THE BACKPLATE TO SUIT WHERE YOU REQUIRE THE MOUNTING SCREWS POSITIONED.

Note: Pipe bracket has a built in safety design feature. Pipes have a slight upward angle to stop floating shelf droop when shelf is loaded. Weight ratings are for E.D.L. (evenly distributed load)

DISCLAIMER: Install our shelf and shelving units according to instructions provided.

We are not responsible for injury or damage resulting from incorrect installation or use.

Our products are for use only as shelves units and are not intended for any other purposes.

For assistance with installation or missing parts, please contact us via customerservice643@gmail.com

*** The emission of the chemicals listed in Prop 65 in this product has been tested to meet the standard of CARB ATCM.**