

STANDARD SERIES UNDERBAR ADD-ON BLENDER STATIONS

MODEL: _____ PROJECT: _____ ITEM #: _____ QTY: _____

PRODUCT IMAGES



18-12BD SHOWN

18-12FT SHOWN

AVAILABLE IN 1800 or 2100 SERIES

STANDARD FEATURES

- **Sink Bowls**
20 gauge stainless steel. 12" Model has 10" x 12" x 7" and 18" Model has 10" x 14" x 7" deep bowl with a 1 1/2" drain located in center
- **Backsplash**
22 gauge stainless steel
- **Sides**
18 gauge stainless steel
- **Back and Bottom**
20 gauge galvanized steel
- **Legs**
1 5/8" tubular 16 gauge galvanized steel with grey plastic bullet foot
- **Shelf**
22 gauge stainless steel
- **Electrical**
Duplex outlet located underneath
- **Plumbing**
1/2" IPS hot and cold water. 1 1/2" IPS drain connection
- **Faucet**
1800 Series: 4" center wall mount faucet
2100 Series: 4" center deck mount faucet
- **Low Lead Compliance**
Low Lead Compliant faucet options are available to meet California AB-1953 and Vermont S152 standards

OPTIONAL ACCESSORIES

- **C-30** Left and Right End Side Splashes
- **30-160** Perforated Dump Basket
- **C-36** Upgrade: Stainless Steel Legs
- **C-39** Right End Side Splash
- **C-40** Left End Side Splash
- **H-109** Upgrade: Royal Series Low Lead Faucet
- **H-200** Upgrade: Commercial Series Low Lead Faucet
- **KR-501** Towel Ring



APPROVED BY:

CERTIFICATIONS:

Due to our commitment to continued product improvement, specifications are subject to change without notice.

Printed in the USA

Krowne Metal Corporation

100 Haul Rd. Wayne, NJ 07470 • Toll Free: (800) 631-0442 • Fax: (973) 872-1129
sales@krowne.com • www.krowne.com • www.facebook.com/KrowneMetal • www.twitter.com/KrowneMetal

Rev. 08/2015
No. 4.11




STANDARD SERIES UNDERBAR ADD-ON BLENDER STATIONS

MODEL: _____ PROJECT: _____ ITEM #: _____ QTY: _____

1800 SERIES: BLENDER STATION


Model Numbers	Length Ⓐ	Left Side to Drain Ⓑ	Bowl Size Ⓓ	Leg Location	Weight (lbs.)
18-12BDR	1'-0"	6"	10" x 12"	Right	30
18-12BDL	1'-0"	6"	10" x 12"	Left	30
18-12BD	1'-0"	6"	10" x 12"	Four	30
18-18BDR	1'-6"	9"	10" x 14"	Right	39
18-18BDL	1'-6"	9"	10" x 14"	Left	39
18-18BD	1'-6"	9"	10" x 14"	Four	39

MECHANICAL REQUIREMENTS: 1/2" IPS hot and cold water. 1 1/2" IPS drain connection



1800 SERIES: FLAT TOP


Model Numbers	Length Ⓐ	Leg Location	Weight (lbs.)
18-12FTR	1'-0"	Right	30
18-12FTL	1'-0"	Left	30
18-12FT	1'-0"	Four	30
18-18FTR	1'-6"	Right	39
18-18FTL	1'-6"	Left	39
18-18FT	1'-6"	Four	39



2100 SERIES: BLENDER STATION


Model Numbers	Length Ⓐ	Left Side to Drain Ⓑ	Bowl Size Ⓓ	Leg Location	Weight (lbs.)
21-12BDR	1'-0"	6"	10" x 12"	Right	30
21-12BDL	1'-0"	6"	10" x 12"	Left	30
21-12BD	1'-0"	6"	10" x 12"	Four	30
21-18BDR	1'-6"	9"	10" x 14"	Right	39
21-18BDL	1'-6"	9"	10" x 14"	Left	39
21-18BD	1'-6"	9"	10" x 14"	Four	39

MECHANICAL REQUIREMENTS: 1/2" IPS hot and cold water. 1 1/2" IPS drain connection



2100 SERIES: FLAT TOP

Model Numbers	Length Ⓐ	Leg Location	Weight (lbs.)
21-12FTR	1'-0"	Right	30
21-12FTL	1'-0"	Left	30
21-12FT	1'-0"	Four	30
21-18FTR	1'-6"	Right	39
21-18FTL	1'-6"	Left	39
21-18FT	1'-6"	Four	39



APPROVED BY:

CERTIFICATIONS:

Due to our commitment to continued product improvement, specifications are subject to change without notice.

Printed in the USA

Krowne Metal Corporation

100 Haul Rd. Wayne, NJ 07470 • Toll Free: (800) 631-0442 • Fax: (973) 872-1129

sales@krowne.com • www.krowne.com • www.facebook.com/KrowneMetal • www.twitter.com/KrowneMetal

Rev. 08/2015
No. 4.11