



Model: _____ Item #: _____ Date: _____

Project: _____ Qty: _____ Approved By: _____

Bar Sinks

Silver Series Underbar



18-53C shown

Available in 1800 or 2100 Series

Standard Features

Sink Bowl	<ul style="list-style-type: none"> ▪ 20 gauge stainless steel ▪ 10" x 14" x 10" deep bowl ▪ 1-1/2" radius on all vertical and horizontal corners ▪ Furnished with 1-1/2" stainless steel drain and 7-1/2" standpipe ▪ Drain located in left rear corner
Drainboard	<ul style="list-style-type: none"> ▪ 20 gauge embossed stainless steel reinforced with welded braces every 6" ▪ 3/4" radius on all vertical and horizontal edges
Front Apron	<ul style="list-style-type: none"> ▪ 22 gauge stainless steel clad over 20 gauge galvanized steel
Backsplash	<ul style="list-style-type: none"> ▪ 22 gauge stainless steel
Sides	<ul style="list-style-type: none"> ▪ 20 gauge stainless steel
Back & Bottom	<ul style="list-style-type: none"> ▪ 20 gauge stainless steel
Legs	<ul style="list-style-type: none"> ▪ 1-5/8" tubular 16 gauge galvanized steel with grey plastic bullet foot
Faucet	<ul style="list-style-type: none"> ▪ 1800 Series: 4" center wall mount faucet ▪ 2100 Series: 4" center wall mount faucet
Low Lead	<ul style="list-style-type: none"> ▪ Low lead compliant faucet options are available to meet California AB-1953 and Vermont S152 standards

Optional Accessories

30-160	Perforated Basket
C-36	Upgrade: Stainless Steel Legs
C-39	Right End Side Splash
C-40	Left End Side Splash
C-66	6" Longer Legs (36" working height)
H-109	Upgrade: Royal Series Faucet
S-"XX"	Single Speedrail ("XX" denotes 24", 30", 36" or 48")
D-"XX"	Double Speedrail ("XX" denotes 24", 30", or 36")
KR-501	Towel Ring





Model: _____ Item #: _____ Date: _____
 Project: _____ Qty: _____ Approved By: _____

Bar Sinks

Silver Series Underbar



1800 Series

Model Numbers	Length A	Drainboard Side B	Left Side to Drain C	Bowls D	Weight (lbs.)
18-22	2'-0"	N/A	4"	2	40
18-31C	3'-0"	12" Each	16"	1	48
18-32L	3'-0"	12" Right	4"	2	53
18-32R	3'-0"	12" Left	15"	2	53
18-42L	4'-0"	24" Right	4"	2	55
18-42R	4'-0"	24" Left	27"	2	55
18-42C	4'-0"	12" Each	15"	2	55
18-33	3'-0"	N/A	4"	3	55
18-43L	4'-0"	12" Right	4"	3	60
18-43R	4'-0"	12" Left	15"	3	60
18-53C	5'-0"	12" Each	15"	3	69
18-63C	6'-0"	18" Each	21"	3	75
18-73C	7'-0"	24" Each	27"	3	86
18-83C	8'-0"	30" Each	33"	3	94
18-64C	6'-0"	12" Each	15"	4	79
18-74C	7'-0"	18" Each	21"	4	91
18-84C	8'-0"	24" Each	27"	4	99

MECHANICAL REQUIREMENTS: 1/2" IPS hot and cold water. 1-1/2" IPS drain connection

2100 Series

Model Numbers	Length A	Drainboard Side B	Left Side to Drain C	Bowls D	Weight (lbs.)
21-22	2'-0"	N/A	4"	2	40
21-31C	3'-0"	12" Each	16"	1	51
21-32L	3'-0"	12" Right	4"	2	56
21-32R	3'-0"	12" Left	15"	2	56
21-42L	4'-0"	24" Right	4"	2	58
21-42R	4'-0"	24" Left	27"	2	58
21-42C	4'-0"	12" Each	15"	2	58
21-33	3'-0"	N/A	4"	3	53
21-43L	4'-0"	12" Right	4"	3	63
21-43R	4'-0"	12" Left	15"	3	63
21-53C	5'-0"	12" Each	15"	3	75
21-63C	6'-0"	18" Each	21"	3	85
21-73C	7'-0"	24" Each	27"	3	95
21-83C	8'-0"	30" Each	33"	3	104
21-64C	6'-0"	12" Each	15"	4	88
21-74C	7'-0"	18" Each	21"	4	100
21-84C	8'-0"	24" Each	27"	4	109

MECHANICAL REQUIREMENTS: 1/2" IPS hot and cold water. 1-1/2" IPS drain connection

