

SYSTEMDEK IIX



DISTRIBUTED BY:
PRO-ACOUSTICS INC.

SYSTEMDEK

IIX

When Systemdek Limited introduced the Model II turntable, it firmly established itself as the authority in offering a fully suspended turntable of audiophile quality at a price which had previously been unattainable. Now, after two years of refinement and further research (and, while others are just now attempting to fall in line with their "budget" turntables), we introduce the Systemdek IIX...

The IIX features an improved suspension system and is now housed in a wooden plinth that rivals any top-of-the-line transcription deck. Major changes in the suspension include a pre-set, three point system in which the floating subchassis is now *hung* on the springs (as opposed to compressing them), resulting in greater stability and eliminating speed variations. Furthermore, the springs have been moved outside the perimeter of the platter, allowing fine tuning *from the top* while a record is playing. No other "budget" turntable, in fact few at any price, offers this kind of dynamic adjustment to optimize one's disc retrieval system. Simplicity of set-up makes the IIX even more attractive, as does the newly designed plinth. Constructed with MDF (Medium Density Fiberboard) for correct resonance in conjunction with the floating system, the unit is finished with fine afromosia veneers and is supplied with dustcover. Proven concepts from Systemdek, such as the machined-in-house glass platter, and a refined oil-pump bearing, remain as integral parts of the IIX, as do the two-speed pulley (driven by a 24-pole synchronous motor) and removeable tonearm mounting board.

The Systemdek IIX is available fitted with the Profile II/Mk2, an improved medium mass tonearm whose qualities readily permit the use of moving coil as well as magnetic cartridges.¹ The "II + II" (Systemdek IIX and Profile II/Mk2) combination offers an even greater value to the user, but with or without tonearm, the Systemdek IIX represents a refined, second generation turntable whose features and sonic merits set new standards for the budget-minded audiophiie.

¹For more information on the Profile II/Mk2 tonearm, ask your dealer for our separate literature sheet.

SPECIFICATIONS

Motor: 24 Pole precision synchronous high torque motor mounted on an anti-vibration assembly.

Power source: 110 — 125V 60Hz.

Power consumption: 3.3VA (approx).

Mains switch: Double Pole with noise suppressor and neon indicator.

Speeds: 33 and 45 RPM (manual change).

Drive system: Precision ground flat rubber belt.

Start-up: 2 seconds to audible stabilisation.

Platter: 3.875lbs (1.73kg) — Glass — 10mm thick.

Record matt: High density lambs wool.

Speed drift: Nil.

Variation under load: 0.15% Ref. 1hr.

Wow and Flutter: 0.09% Din PK weighted.

Rumble 78/77 Din 'B' weighted.

Hum level: 72dB Din 'B' weighted.

Dimensions: 475mm x 375mm x 200mm.

Weight: 22lbs (10kg).

DISTRIBUTED BY:

PRO-ACOUSTICS INC.

Printed in Canada

IN CANADA:

16877 Hymus Blvd.
Kirkland, Quebec H9H 3L4
1-514-694-4790

IN USA:

Waterfront Plaza
Newport, Vermont
05855