



Systems for interiors

ERMETIKA ABSOLUTE EVOKIT | Single and Double Glass Door Plasterboard

Product Specification

Metal cavity door system made of zinc coated metal bars. Model ERMETIKA ABSOLUTE EVOKIT: Cavity width mm 54 for interior walls in plasterboard structures with 75/100mm profiles finished wall size 100/125 mm; Fit for a single door (ABSOLUTE EVOKIT SINGLE DOOR MODEL) or for two opposite doors (ABSOLUTE EVOKIT DOUBLE DOOR MODEL). The doors shall be flat and fit for sliding into a pocket wall. Maximum door weight 100Kg

Passage Opening		
TECHNICAL SHEET		

System components:

3 pre-assembled parts:

horizontal crossbar with anodized aluminium rail

• 6+6 reinforcement bars "omega" shaped with knurled surface

Pre-assembled top profile with anodized aluminum rail

• Edge profiles with appropriate sites to be filled with plaster and leveled

• Floor guide "U" shaped for floor fixing

• 1 spacer + 1 lower alignment bar for squareness

1 standard track kit:
2 trollevs with 4 ball bea

Floor guide for door installation including screws and plugs

Nuts for trolleys, metal plugs for door hanging

2 trolleys with 4 ball bearings 100 kg capacity

Nylon door stopper with fixing screws

Set up:

It is mandatory to keep the system squared and fix it with appropriate tolerance in order to avoid vertical pressure, following accurately the technical instruction provided; after the system is set and plumb, put 12,5 mm plasterboard sheets on each side, using only the screws 3,9x19 provided.

Once the system is installed, do not put weights such as wall furniture, shelves, etc on the wall where the door resides when fully open





Accessories included:

- · Kit for single or double doors
- Frame Seals
- Fittings
- Floor guide
- Glass Clamps
- Soft Close
- Limitation Buffer
- Junction Bar for double doors

Door furniture not included but available to purchase separately:

• Three handle options available without locking mechanism for glass door: The door can be flush with the wall when fully open with some of this handle options (subject to safe installation)

