

ERMETIKA EVOKIT STAFFETTA | Single and Double Door | Plasterboard

Product Specification

Metal cavity door system made of zinc coated metal structure. Model EVOKIT STAFFETTA: cavity width mm 135 for interior walls in plasterboard structures of combined profiles 75/100 mm finished wall size 180 mm; fit for two doors (STAFFETTA SINGLE DOOR MODEL) or for four opposite doors (STAFFETTA DOUBLE DOOR MODEL). The doors shall be flat and fit for sliding into a pocket wall. Maximum track weight 100 kg.

Please note : this model is not fit for full glass doors.

Passage Opening _____

TECHNICAL SHEET

System components:

3 pre-assembled parts:

- front jamb with 2 rotatable joining plates;
- back jamb with 3 rotatable joining plates;
- horizontal crossbar with anodized aluminium rail

- 6+6 reinforcement bars "omega" shaped with knurled surface
- Top profile with central fins for crossbar sliding
- Floor guide "U" shaped for pavement anchorage
- 2 spacers with two bendable lips

● 1 standard track kit:

- 2 trolleys with 4 ball bearings 100 kg capacity
- Floor guide for door installation including screws and plugs
- Nuts for trolleys, metal plugs for door hanging
- Nylon door stopper with fixing screws

Set up:

The system comes in a kit and after assembling the different parts according to the technical sheet is ready for fitting a plasterboard wall.

It is mandatory to keep the system squared and fix it with appropriate tolerance in order to avoid vertical pressure, following accurately the technical instruction provided; after the system is set and plumb, put 12,5 mm plasterboard sheets on each side, using only the screws provided.

Once the system is installed, do not put weights on the wall where the door lays when full open such as wall furniture, shelves, etc..

Kit jambs and architraves:

Wood kit for 42 mm max door, equipped of classic or telescopic architrave.
Components : door jambs, architraves, anti-dust brushes and joints for reception jamb.

wood

Accessories not included but available to purchase separately:

- Soft close Easy-Stop
- Synchro Staffetta - door synchroniser

Door hardware:

- Several handle options available without locking mechanism for wooden door:
The door can be flush with the wall when fully open with some of this handle options (subject to safe installation)

Installation of the Staffetta
Synchronised Kit



Guide to installation Easy
Stop Kit



Accessories:

- Soft close EasyStop
- Synchronization kit;
- 100/120 kg track kit
- Under door profile