

ERMETIKA UNICO EVO | Plasterboard

Product Specification

Metal cavity door system made of zinc coated metal sheets. Model UNICO EVO: cavity width mm 79(x2) for interior walls in plasterboard structures with finished wall size 180 mm; fit for two parallel doors that operate in two opposite directions. The doors shall be flat and fit for sliding into a pocket wall. Maximum door weight 100Kg.

Passage Opening _____

TECHNICAL SHEET

System components:

- double-staved metal panels DX51 Z100
- pre-assembled top profile with "Easyclip" system and anodised aluminum rail
- 2 spacers with two bendable lips
- 1 standard track kit:
 - 2 trolleys with 4 ball bearings 100 kg capacity
 - Floor guide for door installation including screws and plugs
 - Nuts for trolleys, metal plugs for door hanging
 - Nylon door stopper with fixing screws

Set up:

It is mandatory to keep the system squared and fix it with appropriate tolerance in order to avoid vertical pressure, following accurately the technical instruction provided; after the system is set and plumb, put 12,5 mm plasterboard sheets on each side, using only the screws 3,9x19 provided.
Once the system is installed, do not put weights on the wall where the door lays when full open such as wall furniture, shelves, etc..

Kit jambs:

wood

Wood kit for 42 mm max thick door. Components : door jambs, anti-dust brushes.
The Jamb Kit is without any decoration - ready for varnish, stain or paint.

Accessories included:

- Kit for two doors
- Frame Seals
- Fittings
- Under door profile

Accessories not included but available to purchase separately:

- Soft close Easy-Stop Kit
- Self-closing Kit

Door furniture not included but available to purchase separately:

- Round or oblong handle with lock for wooden door:
- double lock latch for internal sliding doors: two opposite hooks come out from the front part of the lock, rotating in closing phase to locate in the plate. The door can be flush with the wall when fully open (subject to safe installation) but available to purchase separately.
- Several handle options available without locking mechanism for wooden door:
The door can be flush with the wall when fully open with some of this handle options (subject to safe installation)

Guide to installation
Easy Stop Kit

