

ERMETIKA EVOKIT | Single and Double Door Plasterboard

Product Specification

Metal cavity door system made of zinc coated metal bars. Model EVOKIT: 12 reinforcement bars; cavity width mm 54/74 for interior walls in plasterboard structures of 75/100 mm finished wall size 100/125 mm; fit for a single door (EVOKIT SINGLE DOOR MODEL) or for two opposite doors (EVOKIT DOUBLE DOOR MODEL). The doors shall be without large raised mouldings and fit for sliding into a pocket wall. Maximum door weight 100Kg.

Passage Opening _____

TECHNICAL SHEET

System components:

- 3 pre-assembled parts:

front jamb with 2 rotatable joining plates;
back jamb with 3 rotatable joining plates;
- 6+6 reinforcement bars "omega" shaped with knurled surface
- Top profile with central fins for crossbar sliding
- Floor guide "U" shaped for floor fixing
- 2 spacers with two bendable lips
- 1 standard track kit:

2 trolleys with 4 ball bearings 100 kg capacity
Floor guide for door installation including screws and plugs
Nuts for trolleys, metal plugs for door hanging
Nylon door stopper with fixing screws

Set up:

It is mandatory to keep the system squared and fix it with appropriate tolerance in order to avoid vertical pressure, following accurately the technical instruction provided; after the system is set and plumb, put 12,5 mm plasterboard sheets on each side, using only the screws 3,9x19 provided.

Once the system is installed, do not put weights such as wall furniture, shelves, etc on the wall where the door resides when fully open

Kit jambs:

wood

Wood kit for 42 mm max thick door. Components : door jambs, anti-dust brushes.
The Jamb Kit is without any decoration - ready for varnish, stain or paint.

Accessories included:

- Kit for single or double doors
- Frame Jambs
- Frame Seals
- Fittings
- Under door profile
- Joining bracket for double doors

Accessories not included but available to purchase separately:

- Soft close Easy-Stop for single or double doors
- Self-closing for single door
- Simultaneous Opening Kit for double doors

Door furniture not included but available to purchase separately:

- Round or oblong handle with lock for wooden door:
- double lock latch for internal sliding doors: two opposite hooks come out from the front part of the lock, rotating in closing phase to locate in the plate. The door can be flush with the wall when fully open (subject to safe installation) but available to purchase separately.

- Several handle options available without locking mechanism for wooden door:
The door can be flush with the wall when fully open with some of this handle options (subject to safe installation)

Pocket Door System Detail & Instructions:

How to install the Evokit
Cassette Frame



Guide to fixing plasterboard
on Evokit Pocket



Guide to installation
the Jamb Kit



Guide to installation
Easy Stop Kit



Double Door Evokit Junction
Bracket Installation

