

DOOR HEIGHT & WIDTH	DOOR THICKNESS	TRACK WIDTH SUPPLIED	TRACK OVERLAP GUIDE FROM CLOSED DOOR EDGE	MINIMUM OVERLAP
1981x610mm	35mm	1500mm	140mm	Minimum overlap of 10mm on both sides and the top of the door compared to the frame aperture, you may decide on more overlap or indeed fitting frame plates but be careful as it will impact on door/track stop.
1981x686mm	35mm	1500mm	64mm	
1981x762mm	35mm	1830mm	153mm	
1981x838mm	35mm	1830mm	77mm	
2040x626mm	40mm	1500mm	124mm	
2040x726mm	40mm	1830mm	179mm	
2040x826mm	40mm	1830mm	89mm	
2040x926mm	40mm	2100mm	124mm	

BESPOKE DOOR SIZES	DOOR THICKNESS	TRACK WIDTH SUPPLIED	MINIMUM OVERLAP
Over 842mm wide and up to 970mm	35 or 40mm	2100mm	Track overlap guide from closed door edge varies from 108mm and down to 80mm - door width dependent.
Over 971mm wide and up to 1000mm	35 or 40mm	2250mm	Track overlap Guide from closed door edge varies from 154mm and down to 75mm - door width dependent.
Over 1001 wide and up to 1150mm	35 or 40mm	2450mm	Track overlap Guide from closed door edge varies from 224mm and down to 75mm - door width dependent.

**BESPOKE DOOR APERTURE HEIGHTS SHOULD BE AT LEAST 10MM SMALLER, WIDTHS SHOULD BE 20MM SMALLER.
EASY TO MEASURE, TAKE THE DOOR APERTURE SIZE - ADD A MINIMUM 20MM TO DOOR WIDTH AND 10MM TO DOOR HEIGHT.**