

PRODUCT DATA

REDIfill is a unique non-toxic multi-purpose woodfiller designed for interior and exterior use, incorporating the latest advances in acrylic and colour technology. REDIfills innovative formulation makes it the most user friendly, colour specific wood and gap filler on the market.

REDIfill is available in 15 Australian colours and 16 American colours that are precisely matched to the most popular timbers used throughout the world. Redifills natural tint base allows you to create your very own colour by mixing in REDI-tints, which are available in Red, Yellow, Brown and Black. These unique concentrated tints can also be added to any of the other colours in the REDIfill range.

REDIfill is fast drying and flexible with no shrinking or sinking which means less work and less time wasted. When REDIfill has dried (15-45 minutes depending on depth of the hole) it can be sanded, painted, tinted, drilled, and polished over. Once REDIfill is opened it will remain reusable as long as the lid is tightly affixed and is kept in a cool dry place. We at REDIfill know that once you have used our filler you will be pleasantly surprised with how easy it is to use whether you may be a home handyman or professional tradesman. For any more information please don't hesitate to contact us directly on: OFFICE +6141559994 MOBILE +61407 147 669.

SIZES AVAILABLE : 260GMS, 500GMS, 1 LTR, 4 LTR, 10 LTR

FEATURES

- COLOUR OXIDE, TINTS OR STAIN CAN BE ADDED
- INDEFINITE SHELF LIFE
- MOLDED INTO THE SHAPE OF TIMBER THAT'S BEEN DISLODGED OR CHIPPED OFF
- CLEAN ALL TOOLS WITH WATER
- EASY TO SAND, NON-TOXIC, NON-FLAMMABLE
- FREEZE AND HEATPROOF
- PROVIDES GOOD FOUNDATION FOR ALL COATINGS TO SIT ON TOP WHETHER IT BE SOLVENT, WATER, OIL OR WAX BASED
- NO WASTAGE, RETURN ANY EXCESS
- MIX COLOURS TOGETHER TO ACHIEVE DESIRED RESULT
- WONT SINK OR SHRINK
- WILL NOT FALL OUT
- FAST DRYING 15-45MINS
- SUITABLE FOR ALL TYPES OF TIMBERS ALSO MDF, PARTICLEBOARD, PLASTERBOARD, VENEER

APPLICATION

HOW TO APPLY REDIFILL

Make sure the surface is clean and free of dust. Fill all holes with a colour that best represents the colour of the wood once it is to be coated. (this latter point is very important). Then apply REDIfill with your thumb, spatula or steel trowel leaving a layer over the hole or small gaps. Allow 15-45 minutes to dry before sanding with a medium to fine sandpaper, clean all tools with water.

REDIFILL USED AS A PUTTY

Putty is used in a wide range of jobs. Whether it be on nail holes or furniture, you want to make sure that the colour is correct by testing it on an off-cut that has been coated. It is always better to have the colour a little darker rather than lighter. Just remember that with our filler you can mix them together to make your own colour. Method of application is usually with your thumb or a spatula. If you are using your thumb or using REDIfill in your hand add a little bit of dust or talc powder to get it to the consistence you want.

REDIFILL USED AS A FLOODFILL OR SLURRY

Floodfilling or a Slurry fill is made by adding a little amount of water until you get a custard like consistency then this can be used on the floor or furniture that has a lot of termite or grain holes on the surface. This form of filling is conducted to reduce unsightly "quilting" (a gap surface tension condition) and on larger floor areas that have small gaps between adjacent boards, for example parquetry. Method of application is usually a rubber squeegee or a steel trowel.

COLOURS AVAILABLE

AUSTRALIAN COLOURS -

JARRAH

WALNUT

BRUSHBOX

MAHOGANY

OAK

HARDWOOD

MIXED HARDWOOD

BLACKBUTT

PINE

CYPRESS PINE

HOOP PINE

MAPLE

CEDAR

EBONY

NATURAL (TINT BASE)

AMERICAN COLOURS-

BRAZILIAN CHERRY

CHERRY

COFFEE

EBONY

GOLDEN BROWN

LIGHT OAK

MAHOGANY

MAPLE-ASH-PINE

PURPLE HEART

RED OAK

SPICED BROWN

WALNUT

WHITE

WHITE OAK

NATURAL BAMBOO

DARK BAMBOO