



## For indoors and outdoors

- solvent-free
- high yield
- weatherproof

**Geeignet für:** Exotic wood, especially red cedar, teak and others, care oil for furniture and decks on yachts, boats and terraces. Contains pigments that effectively block UV-rays and protect against graying and moisture. Teak Oil is satin-matt, anti-skid and protects the surface against algae and moss by drying quickly.

## Anwendung/Verarbeitung:

- Surface has to be clean and free of dust.
- Remove graying with an appropriate detergent.
- Processing temperature (including drying) above 8°C. Wood humidity < 18%. Air humidity < 60%.
- Works differently depending on surface characteristics. A trial coat is necessary.
- Treat softwood (risk of fungi) in outdoor areas with an appropriate impregnation primer before applying the first coat.
- Stir/shake contents well before and during use.
- If possible, apply once on all sides before assembly.
- Apply oil thinly and evenly - avoid layer formation and collect excess oil.

Apply Yacht and Garden Furniture oil to raw, untreated wood by brush, roller or spray nozzle. The wood is weatherproof after two applications. For better saturation of the wood we recommend one application wet-on-wet. Drying takes approximately 12 hours (depending on humidity and temperature). Renew once or twice a year, depending on exposure and after every basic cleaning.

**Verbrauch:** Approximately 60 - 70 ml/m<sup>2</sup>, meaning 1 liter of Teak Oil is enough for approximately 15 m<sup>2</sup> per application, depending on the kind of wood and surface (planed or rough-sawn). Corrugated wood can increase consumption (factor 2 - 3). Lower consumption affects durability of the coat.

**Reinigung:** Clean tools with warm water and soap immediately after use.

**Lagerung:** Cool, but frost free.

**Inhaltsstoffe:** Natural wax, oily binder dispersion, water, iron oxide pigments, emulsifiers, in-can preservatives (1,2-benzisothiazol-3(2H)-one (BIT), reaction mixture made from 5-chloro-2-methyl-2H-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (CIT/MIT), zinc pyrithione; advice for isothiazolinones allergy sufferers + 49 (0)8465 173825).

**Wichtige Hinweise:** Contains reaction mixture made from 5-chloro-2-methyl-2H-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. To avoid skin

Our oral and written technical advice is presented on the the basis of tests and is deemed to be reliable. However, it applies without warranty and does not exempt you from examining the supplied products to confirm their suitability for your particular use and purpose. The application, use and processing of the products are beyond our control, and therefore are entirely your own responsibility. We guarantee of course the specifications in accordance to samples and the consistent quality of our products. The appearance of a new "product information" document supersedes and invalidates any previously published ones.

---

contact use suitable gloves (nitrile). Wear a dust mask when sanding. Safety data sheet available on request. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read carefully and follow all instructions. When using multiple containers with different batch numbers mix them together in a bigger container. Dispose of contents/container in accordance with local regulation. ASN: 080112. EU limit for this product (A/f): 130 g/l. This product contains a maximum of 5 g/l VOC.

**Erhältlich in:** 1 Liter, 2,5 Liter, 10 Liter und größere Menge.

**Farbtöne:**



---

Our oral and written technical advice is presented on the the basis of tests and is deemed to be reliable. However, it applies without warranty and does not exempt you from examining the supplied products to confirm their suitability for your particular use and purpose. The application, use and processing of the products are beyond our control, and therefore are entirely your own responsibility. We guarantee of course the specifications in accordance to samples and the consistent quality of our products. The appearance of a new "product information" document supersedes and invalidates any previously published ones.

**Whittle Waxes**

**Straya**

Factory 13/25 Quanda Road • 04573 Coolum Beach QLD • Australia

Telefon +61 07 5471 7963 • Telefax Emergency number: +61 1300 326 929

E-Mail: [info@whittlewaxes.com.au](mailto:info@whittlewaxes.com.au) • Internet: <http://www.whittlewaxes.com.au>