


KRYLON® INDUSTRIAL PAINT APPLICATION CHART

KRYLON PRODUCT	FORMULA	VOC/MIR COMPLIANT	HIDING	DURABILITY	DRY TIME TO TOUCH	RECOAT WINDOW	CLEAN-UP	CORROSION RESISTANCE	GLOSS	GASOLINE & OIL RESISTANCE
Rust Tough®	Modified Acrylic Enamel	Yes	Best	Best	25 minutes	Before 2 hours or after 2 days	Mineral spirits, turpentine (wet). When dry, lacquer thinner, stripper.	Very good by itself. Excellent with primer.	High	Film does not soften
Rust Tough® Utili-Coat™	Modified Acrylic Enamel	Yes	Best	Best	25 minutes	Before 2 hours or after 2 days	Mineral spirits, turpentine (wet). When dry, lacquer thinner, stripper.	Very good by itself. Excellent with primer.	High	Film does not soften
Eco-Guard™	Acrylic Latex Enamel	Yes	Very Good	Very Good	20 minutes	Anytime	Soap & water (wet). Lacquer thinner, stripper when dry.	Good by itself. Excellent with primer.	High	Film softens after 15 minutes
Interior/Exterior (5-Ball)	Acrylic Lacquerized Enamel	Yes	Good	Good	12 minutes	Anytime (not for use over acrylics)	Lacquer thinner	Excellent with primer.	Medium	Film softens after 15 minutes
Fusion For Plastic™	Modified Acrylic Alkyd	Yes	Very Good	Very Good	15 minutes	Before 24 hours or after 7 days	Lacquer or paint thinner	Very good by itself	High	Film softens after 15 minutes
Tough Coat™	Acrylic Enamel	Yes	Very Good	Very Good	15 minutes	Up to 4 hours or after 5 days	Mineral spirits, turpentine (wet). When dry, lacquer thinner, stripper.	Good by itself. Excellent with primer.	High	Film softens after 15 minutes
ColorWorks™ Maintenance Choice™	Acrylic Enamel	Yes	Good	Good	15 minutes	Before 4 hours or after 5 days	Mineral spirits, turpentine (wet). When dry, lacquer thinner, stripper.	Good by itself. Excellent with primer.	High	Film softens after 15 minutes
SparVar®	Lacquerized Enamel	Yes	Good	Good	15 minutes	Anytime (not for use over acrylics)	Lacquer thinner	Excellent with primer.	Medium	Film softens after 15 minutes
Paint-All™	Acrylic Enamel	Yes	Good	Good	18 minutes	Up to 4 hours or after 5 days	Mineral spirits, turpentine (wet). When dry, lacquer thinner, stripper.	Good by itself. Excellent with primer.	High	Film softens after 15 minutes
Weekend®	Acrylic Enamel	Yes	Good	Good	20 minutes	Up to 4 hours or after 5 days	Mineral spirits, turpentine (wet). When dry, lacquer thinner, stripper.	Good by itself. Excellent with primer.	High	Film softens after 15 minutes
Work Day™	VT Alkyd	Yes	Good	Fair	15 minutes	Before 2 hours or after 3 days	Mineral spirits, turpentine (wet). When dry, lacquer thinner, stripper.	Fair by itself. Very good with anti-rust primer	High	Film softens after 15 minutes



Outdoor Metallic Paints – 16-oz. Aerosol Cans



Non-Skid Coatings – 16-oz. Aerosol Cans



Epoxy Enamel Paints – 16-oz. Aerosol Cans




Appliance Epoxy Spray Paint - 16-oz. Aerosol Cans & Liquid Touch-Up – 2-oz. *



Fluorescent Paints – 16-oz. Aerosol Cans



OSHA Paints – 16-oz. Aerosol Cans



Glowz® Paint – 8-oz. Aerosol Cans – *1-Qt.



Reflect-A-Lite™ – 16-oz. Aerosol Cans



TOUGH COAT® ACRYLIC ENAMELS

Tough Coat® Fluorescent and I.D. Fluorescent Paints – 16-oz. Aerosol Cans



Tough Coat® Appliance Epoxies



Tough Coat® Rebar Green Epoxy – 16-oz. Aerosol Cans

