


LOW HORSEPOWER CHOP SAW WHEELS



Type 1
Low horsepower
chop saw wheels
center reinforced



METAL/STEEL



PART NUMBER	SIZE	MAX RPM	BOX QUANTITY	CASE QUANTITY
A1-11401091	14" x 7/64" x 1"	4,365	10	40

APPLICATIONS

- Steel
- Tubing
- All ferrous metals
- Structural shapes
- Small solid bar stock
- Light bar stock

FEATURES

- Aluminum Oxide grain
- High strength phenolic resin bond
- Center reinforced with high tensile strength fiberglass
- Formulated for low horsepower portable, electric chop saws
- ISO 9001 Certified - Red color code


BENEFITS

- Extended wheel life
- Free and cool cutting
- Strong, durable long-lasting grain
- Less operator fatigue
- Less wear on chop saw

Type 1
Low horsepower
chop saw wheels
double reinforced



METAL/STEEL



PART NUMBER	SIZE	MAX RPM	BOX QUANTITY	CASE QUANTITY
A1-11400991	14" x 3/32" x 1"	4,365	10	50

APPLICATIONS

- Thin wall tube
- Steel studs
- Thin rebar
- Light-gauge metals

FEATURES

- Aluminum Oxide grain
- High strength phenolic resin bond
- Double external reinforced with high tensile strength fiberglass
- Formulated for low horsepower, portable, electric chop saws
- ISO 9001 Certified - Red color code

BENEFITS

- Extended wheel life
- High strength for added safety
- Less operator fatigue
- Less wear on chop saw
- Narrow kerf
- Strong, durable, long-lasting grain

WARNING: Always use tools with guards & wear protective equipment.



II BONDED ABRASIVES II

1-855-817-8390
www.continentalabrasives.com