Collated Nails | Wire Coil 15° Ring Shank

- Bostitch N80CB, N86C & N100C, N100CPP, N130C-2
- Hitachi NV65AB, NV65AC, (up to 2-1/2")
- Hitachi NV83A (up to 3-1/4")
- · Hitachi NV75AG (.099" to .131" 1-3/4" to 3")
- · Makita AN621 1-3/4" to 2-1/2"), AN901 (1-3/4" to 3-1/2")
- MAX CN70 (to 2-3/4"), CN80, HN75, HN90
- MAX 80F, CN100 (2-1/2" to 4")
- MAX CN5655 (1-3/4" to 2-1/2"), CN890II
- MAX CN565 (1-1/2" to 2-1/2"), CN890S
- MAX CN665, CN565D (1-3/4" to 2-1/2")
- MAX CN565S (1-3/4" to 2-1/2")
- Paslode 4275/CN70 (2" to 2-1/2")
- · Paslode 5325/CN80, 5350C
- Paslode 5300 (up to 3")
- · Paslode F275C, F325C
- Paslode P350C (1-1/2" to 3-1/4")
- Paslode P275C (1-1/2" to 2-3/4")
- Porter Cable Coil 350 (up to 3-1/2", Coil 250 (up to 2-1/2")
- Senco SCN56 (up to 2-1/2")
- Senco SCN60 (2" to 2-1/2")
- Senco SCN65 (2" to 3-1/2")
- Senco SCN300 (1-3/4" to 3")

Part #	Penny Size	Length	Shank Diameter	Head Size	Box Count	Box Weight
T12A225PNJ	7d	2-1/4"	.099"	1/4"	1,800	10
T12A250PNJ	8d	2-1/2"	.099"	1/4"	1,800	10
T11A300PNJ	10d	3"	.120"	17/64"	1,800	19
T11A325PNJ	12d	3-1/4"	.120"	17/64"	1,800	20