FORGED HAMMER TOOLS



Removing scale, rust and concrete spatter					
SHANK STYLE	DESCRIPTION	PART NO.	LIST PRICE	WT. (Ibs)	
	12" OAL X 2"	SC-12S	\$49.00	1.6	
SPLINE*	12" OAL X 3"	SC-312S	81.00	2.3	
	18" OAL X 2"	SC-18S	54.00	2.4	
	12" OAL X 2"	SC-12MX	52.00	1.6	
	12" OAL X 3"	SC-312MX	81.00	2.5	
SDS-max	18" OAL X 2"	SC-18MX	60.00	2.4	
SDS-max	18" OAL X 3"	SC-318MX	101.00	2.3	
	24" OAL X 2"	SC-24MX	123.00	2.6	
	36" OAL X 2"	SC-36MX	143.00	4.0	
SDS+	10" OAL X 1 1/2"	SC-12DS	49.00	0.8	
3/4" Hex	12" OAL X 2"	SC-12HX	49.00	1.6	
J/4 ⊓ex	12" OAL X 3"	SC-312HX	53.00	2.5	

COLD CHISELS

· Edging, chipping and channeling concrete, masonry or brick

SHANK STYLE	DESCRIPTION	PART NO.	LIST PRICE	WT. (lbs)
SPLINE*	12" OAL X 1"	CC-12S	\$27.00	1.4
SPLINE	18" OAL X 1"	CC-18S	38.00	2.3
	12" OAL X 1"	CC-12MX	35.00	1.4
	18" OAL X 1"	CC-18MX	41.00	2.3
SDS-max	24" OALX 1"	CC-24MX	92.00	2.6
	36" OALX 1"	CC-36MX	114.00	3.8
SDS+	10" OAL X 3/4"	CC-12DS	37.00	0.8
0/4" Hov	12" OAL X 1"	CC-12HX	27.00	1.4
3/4" Hex	18" OAL X 1"	CC-18HX	35.00	2.3

BUSHING TOOLS

• Roughing concrete surface prior to applying a surface finish

NAMES OF TAXABLE PARTY.	
and the second se	

ONE-PIECE

SHANK STYLE	DESCRIPTION	PART NO.	LIST PRICE	WT. (Ibs)	
SPLINE*	1 pc Bushing Tool	BT-16S	\$129.00	2.6	
SDS-max	1 pc Bushing Tool	BT-16MX	133.00	2.6	
Carbide bu	Carbide bushing tool head is 1 1/2" x 1 1/2"				

and the second se	
and the second second	

TWO-PIECE

SHANK STYLE	DESCRIPTION	PART NO.	LIST PRICE	WT. (Ibs)
SPLINE*	Bushing Head Shk	BS-8S	\$31.00	1.0
SDS-max	Bushing Head Shk	BS-8MX	36.00	1.0
16 Pt	. Bushing Head	BH-16	54.00	1.1
Duching to	ol bood in 1 16" x 1 16	"		

Bushing tool head is 1 1/2" x 1 1/2"

CARBIDE BUSHING TOOLS (ONE-PIECE)

	-			/	
5	SHANK STYLE	DESCRIPTION	PART NO.	LIST PRICE	WT. (lbs)
	SPLINE*	1 pc Bushing Tool	BT-16CS	\$384.00	3.0
112	SDS-max	1 pc Bushing Tool	BT-16CMX	390.00	3.0
P.	Carbide Bushing Tools have 16 carbide points				

Carbide bushing tool head is 1 1/2" x 1 1/2"

GROUND ROD DRIVERS

• Driving electrical grounding rods into earth

SHANK STYLE	DESCRIPTION	PART NO.	LIST PRICE	WT. (Ibs)
SPLINE*	for 5/8" - 3/4" rebar	DR-S	\$133.00	1.1
SDS-max	for 5/8" - 3/4" rebar	DR-MX	139.00	1.1

BULL POINTS or MOIL POINTS

- Breaking up concrete, brick, asphalt, etc.
- Light demolition applications
- Starting holes in concrete slabs

SHANK STYLE	DESCRIPTION	PART NO.	LIST PRICE	WT. (lbs)
SPLINE*	12" OAL	BP-12S	\$27.00	1.4
SFLINE	18" OAL	BP-18S	38.00	2.3
	12" OAL	BP-12MX	33.00	1.4
SDS-max	18" OAL	BP-18MX	39.00	2.3
SDS-max	24" OAL	BP-24MX	93.00	2.6
	36" OAL	BP-36MX	115.00	3.9
SDS+	10" OAL	BP-12DS	37.00	0.8

CLAY SPADE

• Digging clay, dirt, hard-packed gravel, shale, etc.

SHANK STYLE	DESCRIPTION	PART NO.	LIST PRICE	WT. (Ibs)
SPLINE*	4½" X 5½" X 15½"	CS-S	\$158.00	4.8
SDS-max	4½" X 5½" X 15½"	CS-MX	162.00	4.2

ASPHALT CUTTER

 Cutting asphalt or hard ground – not for concrete 	 Cutting 	asphalt o	r hard	around -	not for	concrete
---	-----------------------------	-----------	--------	----------	---------	----------

SHANK STYLE	DESCRIPTION	PART NO.	LIST PRICE	WT. (Ibs)
SDS-max	3½" X 4½" X 15½"	AC-MX	\$195.00	4.3

* Please note! Spline Shank Hammer Iron will not have Splines on the Shank.