

Stationary Cut-Off and Chop Saw Wheels – Double Reinforced

METAL



FEATURES

- Aluminum Oxide grain
- High strength phenolic resin bond
- Double external reinforced with high tensile strength fiberglass

BENEFITS

- Strong, durable, long-lasting grain
- Extended wheel life
- High strength for added safety

APPLICATIONS

- All ferrous metals
- Steel
- Structural steel
- Rebar
- Bar stock

PART #	SIZE	MAX RPM	WHEELS		CS WT LBS
			/BOX	/CASE	
600040	10" x 1/8" x 5/8"	6,100	10	50	45
600050	10" x 1/8" x 1"	6,100	10	50	45
600060	12" x 1/8" x 1"	5,100	10	40	46
600070	14" x 1/8" x 1"	4,400	10	40	65
600080	16" x 1/8" x 1"	3,800	10	40	80
600090	16" x 5/32" x 1"	3,800	10	30	85
600100	18" x 5/32" x 1"	3,400	5	20	77
600110	20" x 5/32" x 1"	3,000	5	20	90



MASONRY



FEATURES

- Silicon Carbide grain
- High strength phenolic resin bond
- Double external reinforced with high tensile strength fiberglass

BENEFITS

- Continuous sharp, aggressive cutting wheel edge
- Extended wheel life
- High strength for added safety

APPLICATIONS

- Masonry products: brick, block, roof tile
- Concrete
- Reinforced concrete
- Stone, artificial stone

PART #	SIZE	MAX RPM	WHEELS		CS WT LBS
			/BOX	/CASE	
601050	10" x 1/8" x 1"	6,100	10	50	50
601060	12" x 1/8" x 1"	5,100	10	40	40
601070	14" x 1/8" x 1"	4,400	10	40	55

