

# A60Q

Amp-Trap® Form 101

HIGH SPEED FUSES



A60Q Amp-Trap® Form 101 high speed fuses feature the only 600V AC / DC rating in the industry of similar size (1-1/2" x 13/32") fuses protecting semiconductors. A60Q also has the lowest I²t of all similar fuses and excellent cycling ability. Applications include inverters and small equipment requiring extremely fast response to faults, without the need to carry sustained heavy overloads.

### FEATURES/BENEFITS:


- Lowest I²t of any fuse this size for greater protection
- Excellent cycling ability gives advantage in equipment design
- 600V AC / DC rated

Catalog Numbering System				
A	60	Q	30	-2
Amp-Trap® Fuse	Rated Volts - 600	Style	Amperes*	Mounting Types* Ferrule, midget dims. (1 1/2" x 13/32"): 2

\* For ampere ratings and styles not listed, call Technical Services at 978-465-4853.

### CATALOG NUMBERS (AMPS)

A6005-2	A60Q12-2	A60Q30-2
A6006-2	A60Q15-2	A60Q35-2
A6008-2	A60Q20-2	A60Q40-2
A60Q10-2	A60Q25-2	



### RATINGS

- **Volts:** 600VAC/DC
- **Amps:** 5 to 40A (AC); 5 to 40A (DC)
- **I.R.:** 200kA I.R. AC, 100kA I.R. DC
- **L/R:** 10ms

### HIGHLIGHTS:

- 600VAC/DC rated
- Extremely fast acting
- Current limiting
- Lowest I²t
- Excellent cycling ability

### APPLICATIONS:

- Protection of small inverters and drives, and equipment requiring the highest degree of protection

### APPROVALS:



- UL Recognized component
- AC: UL guide JFHR2 File E60314
- DC: UL file E60314

### FUSE HOLDERS FOR A60Q FUSES:

- USM Series      UltraSafe™ Fuse Holders
- 303 Series      Midget Fuse Blocks

Mersen products have been designed by Mersen for a range of specific applications to be operated depending on particular specification and conditions. Mersen makes no representation or/and warranty, and waives any liability, either express or implied for products' reliability and life time or technical performance in case Mersen has not been provided with customer's specifications or if the products are not purchased directly from Mersen or its distributors and/or agents.