BS 5 Lever & 5 Lever Mortice

2100S

BS 5 Lever StrongBOLT



Application:

Specification:

For timber doors hinged on the left or rightSuitable for doors up to 54mm thick
 Suitable for doors up to sufficient thick Deabolt locked or unlocked by the key from either side 20mm deadbolt for secure positive deadlocking and additional resistance against attack 2100S can be keyed alike with 2200S Anti-pick, anti-saw and anti-drill security features for resistance against attack Chamfered bolt design increases the performance of the lock under side load testing. The chamfer of the bolt also makes drilling attack more difficult Supplied with covered escutcheon to match forend Radius inner forend for ease of installation Can be installed in the many UK mortices without the need for additional carpentry or spoiling the edge of the door Anti-pick and keyhole protection prevents forced entry by picking Hardened steel pins provide resistance to attack from sawing Case Size: 67mm (2.5") or 79.5mm (3") Backset: 45mm or 57.5mm Case: Steel, red powder coat Forend: Stainless steel or brass Striking Plate: Finished to match forend Faceplate: Supplied with square faceplate which covers a radius inner forend Deadbolt: Brass with hardened steel rollers Latch Bolt: n/a Follower: n/a Rebate Kit: 2100REB 13mm (0.5") Keying Groups: May be supplied to pass or differ. Supplied with 2 steel nickel plated keys Key Blank Number: KB430 NB: Not suitable for master keying Packaging: Individually boxed, supplied in outer boxes of 10

Finish:

SC - Satin ChromePL - Satin Brass





Standards:

- Tested to BS3621:2007 2 H 4 1 0 F 7 K D 0 B
- EN 1634-1 assessed for use on 60 minutes timber fire doors



2100S

BS 5 Lever StrongBOLT

UNIDN[®] ASSA ABLOY

