# **2 Lever Mortice**

## 2295

### **2 Lever Mortice Lock**



Application:	<ul><li>For timber doors hinged on the left or right</li><li>Keys suitable for doors up to 54mm thick</li></ul>	
Specification:	<ul> <li>Deadbolt locked or unlocked by key from either side</li> <li>Latch bolt withdrawn by lever handle from either side</li> <li>Reversible latch bolt</li> <li>Two way action, suitable for lightweight knobs or sprung handles</li> <li>Not suitable for bolt through fixings</li> <li>Available with square forend and locking plate</li> <li>Case Size: 63mm (2.5") or 76mm (3")</li> <li>Backset: 44.5mm or 57mm</li> <li>Case: Steel, black powder coat</li> <li>Forend: Chrome or brass finish</li> <li>Striking Plate: Finished to match forend</li> <li>Deadbolt: Aluminium</li> <li>Latch Bolt: Aluminium</li> <li>Follower: 8mm square</li> <li>Keying Groups: May be supplied to pass, differ &amp; keyed alike with 2242. Supplied with 2 zinc nickel plated keys. NB: Not suitable for master keying</li> <li>Key blanks not sold separately</li> <li>Keying: 20 standard differs (M21H - M40H)</li> </ul>	Standards • EN 163 timber
Finish:	<ul> <li>CH - Polished Chrome finish</li> <li>PL - Polished Brass finish</li> </ul>	
Technical Design:	63mm or 11mm 76mm	22mm



#### s:

34-1 assessed for use on 60 minutes fire doors

#### 22mm 0 152.5mm 101mm 12.5mm 102mm 57mm 0 12.5mm 0 44.5mm or U 12.5mm 57mm