

# SMALL SMART DISCREET



Smart thinking. NANO has arrived. Little lockers, doors and drawers will love NANO90.

NANO90 is the ideal keyless solution to upgrade and replace locks on lockers, cupboard doors and drawers. Fit the product in place of standard cam locks, NANO90 can be surface mounted or flush fitted for a really sleek look. Whether installed on lockers, mail boxes, courier drop boxes or medical cabinets, just simply enter a four digit code, lock and go!







On the door programming



Two year guarantee\*



Private and Public Functions

### **FEATURES**

- 12 button keypad
- 8 digit Master and Sub-Master Code
- 4 digit User Code
- 6 digit Technician Code
- Left hand and right hand versions available
- Up to 100,000 operations from 1 x coin cell battery (supplied)
- Suitable for doors up to 400 x 400mm
- Battery override
- Auto unlock feature
- All parts / fixings / templates included



### **FUNCTIONS**





#### **Private Function**

This is the default function and is already pre-programmed in new locks. This function is used where the same code will be repeatedly used, e.g. an employee with the same locker/drawer in the workplace.





#### **Public Function**

In this function the KitLock operates with a single User Code. The user enters a personal four digit code, this locks the lock. The same code is entered once only to open the lock before automatically being erased and ready for the next user. This function is used for short term, multiple occupancy applications, e.g. hot desking in an office or a locker in a sports club.

#### PRODUCT DIMENSIONS

# $30\text{mm} \left(1^{3}/_{16}\right)$

1

## ACTUAL SIZEL

#### **Code Management**

NANO90 has four code levels available:

- 8 digit Master Code
- 8 digit Sub-Master Code
- 4 digit User Code
- 6 digit Technician Code

The KitLock is supplied with two factory set codes:

- Master Code
- User Code

Before installing, change the Master and User Code by following the Programming and Operating Instructions.



#### TECHNICAL SPECIFICATIONS

FEATURE	DESCRIPTION
Operations	Up to 100,000 opening per 1 x coin cell battery
Battery Override	A 9 volt PP3 battery can be placed against external contacts
Low Battery Warning	Red LED will flash on opening to indicate low battery
Functions	Private and Public
Buttons	12 individual buttons
Material	ABS
Finish Colour	Silver grey standard Black also available
Door Thickness	Surface mounted up to 25mm (1") Flush fitted up to 40mm (15/8")
Memory	Non-volatile memory will be retained
Fitting	Easy to install and program
Fitting Options	Vertical, right hand and left hand models
Auto Unlock Program	Set lock to open after a set time

Note: Not suitable for Chlorine environments.



30mm (3<sup>9</sup>/<sub>16</sub>")







