

IS65

ISEO®

1 Preparation of the lock body and marking of the door edge. Tools: M5 screws (Ø2,5, Ø4,2), power drill.

2 Mounting the lock body into the door edge.

3 Mounting the handle and spindle.

4 Mounting the handle plate and adjusting the handle height.

5 Mounting the handle plate and adjusting the handle height.

6 Final assembly and adjustment of the lock mechanism.

7 Final assembly and adjustment of the lock mechanism.

Dimensions: 180°, ≤950

CE mark and technical data:

| | | |
|-----------------------------|---|---|
| CE | ISEO Serrature S.p.A. Via S. Girolamo, 13 25055 - Pisogne - BS Italy | 16 |
| | 0432-CPR-00026-89.08 | EN1154:1996/A1:2002/AC:2006 4 8 3 1 1 3 |
| Dangerous substances : None | | |

KW-IS65 made in PRC

for DoP CPR305/2011/EU iseo.com/dop

ISEO Serrature s.p.a. Via San Girolamo 13 25055 Pisogne (BS) Italy

Tel +39 0364 8821 Fax +39 0364 882263 iseo@iseo.com www.iseo.com

Dimensions: 147, 193, 100, 45, 12,5, 23, <8mm, 180°, 15°

Warning: Paper templates might distort due to air moisture. Only the indicated measurements are therefore binding. Les gabarits en papier peuvent avoir des dimensions modifiées par l'humidité de l'air. Seules les cotes mentionnées doivent être respectées. Le digne di carta possono alterarsi per colpa dell'umidità. Perciò sono vincolanti solo le quote indicate. Montagematériel av papíer kan torändras i storlek av luftfuktighet. Endast de angivna måttuppgifterna är därför helt tillförlitliga. Papír skablonen kan torändras sig p.g.a. luftfugtighed. Derfor er kun de angivne mål bindende. Kostüden lõhdoosa võivad papirsen asemuskäaaron muutuda. Stõvoia ova! siiski arvestaasaan armetut määta. Papiimatier kan torändras seg p.g.a. luftfuktighet. Det er derfor bare de angitte mål som er fornlidlige. Las plantillas de montaje de papel pueden variar su tamaño por causa de la humedad. Las dimensiones reales son las indicadas en la misma.

IS65

ISEO®

1 Preparation of the lock body and marking of the door edge. Tools: M5 screws (Ø2,5, Ø4,2), power drill.

2 Mounting the lock body into the door edge.

3 Mounting the handle and spindle.

4 Mounting the handle plate and adjusting the handle height.

5 Mounting the handle plate and adjusting the handle height.

6 Final assembly and adjustment of the lock mechanism.

7 Final assembly and adjustment of the lock mechanism.

Dimensions: ≤950

CE mark and technical data:

| | | |
|-----------------------------|---|---|
| CE | ISEO Serrature S.p.A. Via S. Girolamo, 13 25055 - Pisogne - BS Italy | 16 |
| | 0432-CPR-00026-89.08 | EN1154:1996/A1:2002/AC:2006 4 8 3 1 1 3 |
| Dangerous substances : None | | |

KW-IS65 made in PRC

for DoP CPR305/2011/EU iseo.com/dop

ISEO Serrature s.p.a. Via San Girolamo 13 25055 Pisogne (BS) Italy

Tel +39 0364 8821 Fax +39 0364 882263 iseo@iseo.com www.iseo.com

Dimensions: 428, 45, 12,5, 23, 5,2, 32, 54, <70mm, 180°, 15°

